

Bellcourt

Product Type	Broadloom	
Collection	Lush Life	
Style Number	5B094	
Construction	Cut Pile	
Fiber	Ecosolution Q® Nylon	
Primary Backing	Synthetic	
Secondary Backing	Classicbac®	
Protective Treatments	Srs® Stain Resistance Treatment	
Recommended Adhesive	H1000, H1200 or H3800	
	metric	U.S.
Product Size	3.66 m	12 ft
Gauge	39.4 per 10 cm	1/10 in
Stitches	49.0 per 10 cm	12.5 per in
Average Density	0.187 g/cm³	5043 oz/yd³
Kilotex	11.75	
Total Thickness	9.91 mm	0.390 in
Tufted Weight	1220.6 g/m²	36 oz/yd²
Installation Pattern Repeat	45.72 cm w x 45.72 cm l	18" w x 18" l

Recommended Installation Method

Direct Glue, Double Glue, Stretch-In

Performance + Testing

Pill Test	Pass
Radiant Panel	Class I
NBS Smoke	Less Than 450
Electrostatic Propensity	Less Than 3.5 kv
ADA Compliance	>0.6, Meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes***

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

20 Year Commercial Limited

Material Health & Environmental Certifications

Total Recycled Content	<1% (Pre-Consumer <1% Post-Consumer 0%)
Country of Origin**	USA

Coordinating Products

Broadloom: **Moritz, Kennebunk, Cranford**

Available Colorways



Additional Information

***This carpet is manufactured to be ADA compliant, but to be fully ADA compliant, the end-user must ensure the carpet is adhered to the floor and installed as outlined in the ADA standards.

[Installation Guidelines](#)

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.