

Inhabit Sheet

Collection	<b>Abide &amp; Inhabit</b>	
Style Number	<b>4106V</b>	
Welding Rod Style Number	<b>353VS</b>	
Construction	<b>Commercial Heterogeneous Sheet With Fibreglass</b>	
Class / ASTM F1303	<b>Type I, Grade 1, Class B</b>	
Finish	<b>ExoGuard+®</b>	
	U.s.	Metric
Wear Layer Thickness	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Overall Thickness	<b>0.087 in</b>	<b>2.2 mm</b>
Installation Type	<b>Dry Back</b>	
Installation	<b>Direct Glue</b>	
Recommended Adhesive	<b>S150 Resilient Sheet Spray 1 Can, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, , SHAW 4100 or 4151</b>	

Packaging

Actual Roll Size	<b>6.56 ft w x 68.58 ft l</b>	<b>2.00 m w x 20.90 m l</b>
Area Per Roll	<b>50 sy/roll</b>	<b>41.81 sq m/roll</b>
Weight Per Roll	<b>337.7 lbs</b>	<b>153.18 kg</b>



Recommended Installation Method



Reverse

Coordinating Products

Sheet: Inhabit Plus Sheet  
LVT: Abide

Performance + Testing

Static Load (ASTM F970)	<b>Passes (Modified), *1500 lbs</b>	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	<b>Passes</b>	
Flexibility (ASTM F137)	<b>Passes</b>	
Resistance to Heat (ASTM F1514)	<b>Passes</b>	
Resistance to Light (ASTM F1515)	<b>Passes</b>	
Resistance to Chemicals (ASTM F925)	<b>Passes</b>	
Radiant Panel (ASTM E648)	<b>Passes, Class I</b>	
coefficient of friction (ASTM D2407, slip resistance)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing	
Indoor Air Quality	FloorScore®   Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   3rd Party Certified Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	<b>FloorScore® Certified</b>
EQ Credit: Low Emitting Materials	
Option 1: Product Category Calculations	

[Installation Guidelines](#)

Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways



Oyster Shell Oak 06140  
V3 - Moderate Variation  
Weldrod 06140



Antique Oak 06150  
V3 - Moderate Variation  
Weldrod 12761




Grain Wenge 06210  
V2 - Slight Variation  
Weldrod 09633



Barley Oak 06220  
V3 - Moderate Variation  
Weldrod 06220



Sesame Oak 06240  
V3 - Moderate Variation  
Weldrod 07325




Honey Wenge 06250  
LRV 23.8 | L\* 55.84  
V2 - Slight Variation  
Weldrod 09634



Palladium Oak 06515  
V3 - Moderate Variation  
Weldrod 02020



Liquorice Oak 06570  
V4 - Substantial Variation  
Weldrod 02026




Ginger Oak 06630  
V4 - Substantial Variation  
Weldrod 05257



Buckskin Oak 06660  
V3 - Moderate Variation  
Weldrod 02025



Nubuck Oak 06700  
V4 - Substantial Variation  
Weldrod 05211



Clove Walnut 06710  
V3 - Moderate Variation  
Weldrod 05211



Cummin Oak 06720  
V3 - Moderate Variation  
Weldrod 02025



Cameroon Wenge 06730  
V2 - Slight Variation  
Weldrod 09561



Cocoa Walnut 06760  
V3 - Moderate Variation  
Weldrod 01823



Sable Oak 06780  
V3 - Moderate Variation  
Weldrod 0732D

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

