

Inhabit Sheet

Collection	Abide & Inhabit	
Style Number	4106V	
Welding Rod Style Number	353VS	
Construction	Commercial Heterogeneous Sheet With Fibreglass	
Class / ASTM F1303	Type I, Grade 1, Class B	
Finish	ExoGuard+®	
	U.s.	Metric
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.087 in	2.2 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150 Resilient Sheet Spray 1 Can, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, , SHAW 4100 or 4151	

Packaging

Actual Roll Size	6.56 ft w x 68.58 ft l	2.00 m w x 20.90 m l
Area Per Roll	50 sy/roll	41.81 sq m/roll
Weight Per Roll	337.7 lbs	153.18 kg

Recommended Installation Method



Reverse

Coordinating Products

LVT: Abide
Sheet: Inhabit Plus Sheet

Performance + Testing

Static Load (Astm F970)	Passes (Modified), *1500 lbs	*This Test Is Intended To Compare Relative Properties Of Different Styles And Constructions. Results Are Based On A Laboratory Test And Used For Comparative Purposes - Real Life Load Limit May Vary.
Residual Indentation (Astm F1914)	Passes	
Flexibility (Astm F137)	Passes	
Resistance To Heat (Astm F1514)	Passes	
Resistance To Light (Astm F1515)	Passes	
Resistance To Chemicals (Astm F925)	Passes	
Radiant Panel (Astm E648)	Passes, Class I	
Coefficient Of Friction (Astm D2407, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications



Health & Wellbeing	
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 3rd Party Certified
	Country of Origin Imported


Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.


Visit shawcontract.com/testing for more information.

Available Colorways


					
Oyster Shell Oak 06140 V3 - Moderate Variation Weldrod 06220	Antique Oak 06150 V3 - Moderate Variation Weldrod 09633	Grain Wenge 06210 V2 - Slight Variation Weldrod 09634	Barley Oak 06220 V3 - Moderate Variation Weldrod 05257	Sesame Oak 06240 V3 - Moderate Variation Weldrod 07325	Honey Wenge 06250 LRV 23.8 L* 55.84 V2 - Slight Variation Weldrod 02025




Palladium Oak 06515
V3 - Moderate Variation
Weldrod 05211




Liquorice Oak 06570
V4 - Substantial Variation
Weldrod 09561




Ginger Oak 06630
V4 - Substantial Variation
Weldrod 06140




Buckskin Oak 06660
V3 - Moderate Variation
Weldrod 02025




Nubuck Oak 06700
V4 - Substantial Variation
Weldrod 05211




Clove Walnut 06710
V3 - Moderate Variation
Weldrod 01823




Cumin Oak 06720
V3 - Moderate Variation
Weldrod 02020



Cameroon Wenge 06730
V2 - Slight Variation
Weldrod 12761



Cocoa Walnut 06760
V3 - Moderate Variation
Weldrod 02026




Sable Oak 06780
V3 - Moderate Variation
Weldrod 0732D

Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1




Uniform Appearance

V2




Slight Variation

V3



Moderate Variation

V4



Substantial Variation