

Inhabit Sheet

Colección	Abide & Inhabit	
Número De Estilo	4106V	
Número De Estilo De Barra De Soldadura	353VS	
Construcción	Manta Vinílica Comercial Heterogénea Con Fibra De Vidrio	
clase	Type I, Grade 1, Class B	
Terminación	ExoGuard+®	
	U.s.	Metric
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.087 in	2.2 mm
Installation Type	Dry Back	
Instalación	Direct Glue	
Adhesivo Recomendado	S150 Resilient Sheet Spray 1 Can, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, , SHAW 4100 or 4151	

Embalaje

Tamaño Real Del Rollo	6.56 ft w x 68.58 ft l	2.00 m w x 20.90 m l
Área Por Rollo	50 sy/roll	41.81 sq m/roll
Peso Por Rollo	337.7 lbs	153.18 kg



Método De Instalación Recomendado



Inverso

Productos Que Combinan

LVT: Abide

desempeño + pruebas

carga estática (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
margen adicional residual (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
resistencia al calor (ASTM F1514)	Passes	
resistencia a la luz (ASTM F1515)	Passes	
resistencia a productos químicos (ASTM F925)	Passes	
panel radiante (ASTM E648)	Passes, Class I	
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificaciones

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado Tercerizado
	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore® Certified

[Installation Guidelines](#)

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways



Oyster Shell Oak 06140
V3 - Moderate Variation
Weldrod 06140



Antique Oak 06150
V3 - Moderate Variation
Weldrod 12761




Grain Wenge 06210
V2 - Slight Variation
Weldrod 09633



Barley Oak 06220
V3 - Moderate Variation
Weldrod 06220



Sesame Oak 06240
V3 - Moderate Variation
Weldrod 07325




Honey Wenge 06250
LRV 23.8 | L* 55.84
V2 - Slight Variation
Weldrod 09634



Palladium Oak 06515
V3 - Moderate Variation
Weldrod 02020



Liquorice Oak 06570
V4 - Substantial Variation
Weldrod 02026




Ginger Oak 06630
V4 - Substantial Variation
Weldrod 05257



Buckskin Oak 06660
V3 - Moderate Variation
Weldrod 02025



Nubuck Oak 06700
V4 - Substantial Variation
Weldrod 05211



Clove Walnut 06710
V3 - Moderate Variation
Weldrod 05211



Cummin Oak 06720
V3 - Moderate Variation
Weldrod 02025



Cameroon Wenge 06730
V2 - Slight Variation
Weldrod 09561



Cocoa Walnut 06760
V3 - Moderate Variation
Weldrod 01823



Sable Oak 06780
V3 - Moderate Variation
Weldrod 0732D

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

