

Inhabit Sheet


Coleção	Abide & Inhabit	
Número Do Produto	4106V	
Número Do Estilo Da Haste De Soldagem	353VS	
Construção	Manta Comercial Heterogênea Com Fibra De Vidro	
classe	Type I, Grade 1, Class B	
Acabamento	ExoGuard+®	
	U.s.	Metric
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.087 in	2.2 mm
Installation Type	Dry Back	
Instalação	Direct Glue	
Adesivo Recomendado	S150 Resilient Sheet Spray 1 Can, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, , SHAW 4100 or 4151	

Empacotamento

Tamanho Real Do Rolo	6.56 ft w x 68.58 ft l	2.00 m w x 20.90 m l
Área Por Rolo	50 sy/roll	41.81 sq m/roll
Peso Por Rolo	337.7 lbs	153.18 kg



Método De Instalação Recomendado



Reverso

Produtos Coordenados

LVT: Abide

desempenho + teste

carga estática (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
recuo residual (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
resistência ao calor (ASTM F1514)	Passes	
resistência à luz (ASTM F1515)	Passes	
resistência a produtos químicos (ASTM F925)	Passes	
painel radiante (ASTM E648)	Passes, Class I	
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificações

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado 3rd Party Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	FloorScore® Certified
Crédito de EQ: Materiais de baixa emissão	
Opção 1: cálculos de categoria de produto	

[Installation Guidelines](#)

















Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

 <p>Oyster Shell Oak 06140 V3 - Moderate Variation Weldrod 06140</p>	 <p>Antique Oak 06150 V3 - Moderate Variation Weldrod 12761</p>	 <p>Grain Wenge 06210 V2 - Slight Variation Weldrod 09633</p>	 <p>Barley Oak 06220 V3 - Moderate Variation Weldrod 06220</p>	 <p>Sesame Oak 06240 V3 - Moderate Variation Weldrod 07325</p>	 <p>Honey Wenge 06250 LRV 23.8 L* 55.84 V2 - Slight Variation Weldrod 09634</p>
 <p>Palladium Oak 06515 V3 - Moderate Variation Weldrod 02020</p>	 <p>Liquorice Oak 06570 V4 - Substantial Variation Weldrod 02026</p>	 <p>Ginger Oak 06630 V4 - Substantial Variation Weldrod 05257</p>	 <p>Buckskin Oak 06660 V3 - Moderate Variation Weldrod 02025</p>	 <p>Nubuck Oak 06700 V4 - Substantial Variation Weldrod 05211</p>	 <p>Clove Walnut 06710 V3 - Moderate Variation Weldrod 05211</p>
 <p>Cumini Oak 06720 V3 - Moderate Variation Weldrod 02025</p>	 <p>Cameroon Wenge 06730 V2 - Slight Variation Weldrod 09561</p>	 <p>Cocoa Walnut 06760 V3 - Moderate Variation Weldrod 01823</p>	 <p>Sable Oak 06780 V3 - Moderate Variation Weldrod 0732D</p>		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

