


Inhabit Sheet

Coleção	Abide & Inhabit	
Número Do Produto	4106V	
Número Do Estilo Da Haste De Soldagem	353VS	
Construção	Manta Comercial Heterogênea Com Fibra De Vidro	
classe	Type I, Grade 1, Class B	
Acabamento	ExoGuard+®	
	U.s.	Metric
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.087 in	2.2 mm
Installation Type	Dry Back	
Instalação	Direct Glue	
Adesivo Recomendado	S150 Resilient Sheet Spray 1 Can, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon, SHAW 4100 or 4151	

Empacotamento

Tamanho Real Do Rolo	6.56 ft w x 68.58 ft l	2.00 m w x 20.90 m l
Área Por Rolo	50 sy/roll	41.81 sq m/roll
Peso Por Rolo	337.7 lbs	153.18 kg

Método De Instalação Recomendado



Produtos Coordenados

LVT: Abide

Desempenho + Teste

Recuo Residual (Astm F1914)	Passes
Flexibilidade (Astm F137)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Coeficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Atributos + Certificações

Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	FloorScore® Certificado
	CE Marking (EN 14041) Certificado 3rd Party
	Country of Origin Imported

Crédito De Contribuição


MR Credit: Divulgação e otimização de produtos de construção	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	FloorScore Certified
Crédito de EQ: Materiais de baixa emissão	
Opção 1: cálculos de categoria de produto	
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.


Visit shawcontract.com/testing for more information.

Available Colorways


					
Oyster Shell Oak 06140	Antique Oak 06150	Grain Wenge 06210	Barley Oak 06220	Sesame Oak 06240	Honey Wenge 06250
V3 - Moderate Variation	V3 - Moderate Variation	V2 - Slight Variation	V3 - Moderate Variation	V3 - Moderate Variation	LRV 23.8
Weldrod 06220	Weldrod 09633	Weldrod 09634	Weldrod 05257	Weldrod 07325	V2 - Slight Variation
					Weldrod 02025




Palladium Oak 06515
V3 - Moderate Variation
Weldrod 05211




Liquorice Oak 06570
V4 - Substantial Variation
Weldrod 09561




Ginger Oak 06630
V4 - Substantial Variation
Weldrod 06140




Buckskin Oak 06660
V3 - Moderate Variation
Weldrod 02025




Nubuck Oak 06700
V4 - Substantial Variation
Weldrod 05211




Clove Walnut 06710
V3 - Moderate Variation
Weldrod 01823




Cumin Oak 06720
V3 - Moderate Variation
Weldrod 02020



Cameroon Wenge 06730
V2 - Slight Variation
Weldrod 12761




Cocoa Walnut 06760
V3 - Moderate Variation
Weldrod 02026





Sable Oak 06780
V3 - Moderate Variation
Weldrod 0732D


Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1

Uniform Appearance

V2

Slight Variation

V3

Moderate Variation

V4

Substantial Variation