

Abide

| | | |
|----------------------|--|--------------------------|
| Collection | Abide & Inhabit | |
| Style Number | 4107V | |
| Construction | Heavy Commercial Luxury Vinyl Tile | |
| Class / ASTM F1700 | Class III, Type B | |
| Finish | ExoGuard+® | |
| | U.S. | Metric |
| Nominal Dimensions | 7 in w x 47 in l | 18 cm w x 120 cm l |
| Actual Dimensions | 7.09 in w x 47.24 in l | 18.01 cm w x 119.99 cm l |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Thickness | 0.098 in | 2.5 mm |
| Edge Profile | Squared Edge | |
| Installation Type | Dry Back | |
| Installation | Direct Glue | |
| Recommended Adhesive | S150 Resilient Sheet Spray 1 Can, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|-------------------|-------------|-----------|
| Pieces per Carton | 18 pcs | |
| Area per Carton | 41.85 sq ft | 3.89 sq m |
| Weight per Carton | 38.64 lbs | 17.53 kg |



Recommended Installation Method



Coordinating Products

Sheet: Inhabit Sheet

Performance + Testing

| | | |
|--|---|--|
| Static Load (ASTM F970) | Passes (Modified), *1500 lbs | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |
| Residual Indentation (ASTM F1914) | Passes | |
| Resistance to Heat (ASTM F1514) | Passes | |
| Resistance to Light (ASTM F1515) | Passes | |
| Resistance to Chemicals (ASTM F925) | Passes | |
| Radiant Panel (ASTM E648) | Passes, Class I | |
| Coefficient of Friction (ASTM D2047, Slip Resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes | |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. | | |

Warranties

- Commercial 15 Year Underbed Bond Warranty
- 15 Year Commercial Limited Warranty

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw’s diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Certified |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 6.05 Kg Co ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | |
| | CE Marking (EN 14041) 3rd Party Certified |
| | Country of Origin Imported |

WELL V2 Contribution Credit

- X01 Fundamental Material Precautions
Part 1: (C): Restrict Asbestos Precondition
- X08 Hazardous Material Reduction
Part 1: Limit Hazardous Materials Optimization
- X10 Volatile Compound Reduction
Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization
- X10 Volatile Compound Reduction
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization
- X11 Long Term Emissions Control
Part 2: Flooring Optimization
- X14 Material Transparency
Part 1: Promote Ingredient Disclosure Optimization

- Absence of Asbestos
- Absence of Heavy Metals
- Absence of Halogenated Flame Retardants
- Ortho-Phthalates
- FloorScore Certificate
- Health Product Declaration (HPD) | 1000 Ppm Disclosure

Leed v4 Contribution Credits

- MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting
- MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)
- EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

- Health Product Declaration (HPD) | 1000 Ppm Disclosure
- 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
- FloorScore Certified

[Installation Guidelines](#)
[Maintenance Guidelines](#)






Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Conch Shell Oak 07140 LRV 31.4 L* 62.8 V3 - Moderate Variation | Heirloom Oak 07150 LRV 22.9 L* 54.92 V3 - Moderate Variation | Maize Wenge 07210 LRV 33.5 L* 64.52 V2 - Slight Variation | Wheat Oak 07220 LRV 32.6 L* 63.86 V3 - Moderate Variation | Tahini Oak 07240 LRV 27 L* 58.95 V3 - Moderate Variation | Caramel Wenge 07250 LRV 22.7 L* 54.73 V2 - Slight Variation |
|  |  |  |  |  |  |
| Cadmium Oak 07515 V3 - Moderate Variation | Anise Oak 07570 LRV 13.4 L* 43.36 V4 - Substantial Variation | Spiced Oak 07630 LRV 13.9 L* 44.11 V4 - Substantial Variation | Palomino Oak 07660 LRV 20.3 L* 52.14 V3 - Moderate Variation | Brushed Suede Oak 07700 LRV 13.4 L* 43.36 V4 - Substantial Variation | Allspice Walnut 07710 LRV 12.2 L* 41.53 V3 - Moderate Variation |

| | | | |
|--|---|---|--|
|  |  |  |  |
| Coriander Oak 07720 LRV 20.6 L* 52.5 V3 - Moderate Variation | Gabon Wenge 07730 LRV 10.9 L* 39.35 V2 - Slight Variation | Chocolate Walnut 07760 LRV 9.3 L* 36.48 V3 - Moderate Variation | Raw Umber Oak 07780 LRV 9.3 L* 36.58 V3 - Moderate Variation |

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

