

Abide

Collection	Abide & Inhabit	
Numéro De Style	4107V	
Construction	Carreau De Vinyle De Luxe Commercial Lourd	
classe	Class III, Type B	
Finition	ExoGuard+®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 47 in l	18 cm w x 120 cm l
Dimensions Réelles	7.09 in w x 47.24 in l	18.01 cm w x 119.99 cm l
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.098 in	2.5 mm
Profil Du Bord	Bord Carré	
Installation Type	Dry Back	
Installation	Direct Glue	
Adhésif Recommandé	S150 Resilient Sheet Spray 1 Can, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Emballage

Pièces Par Carton	18 pcs	
Surface Par Carton	41.85 sq ft	3.89 sq m
Poids Par Carton	38.64 lbs	17.53 kg



Méthodes d'Installation Conseillées



Coordination Des Produits

Sheet: Inhabit Sheet

Performance + Tests Et Essai

Charge Statique (Astm F970)	<b>Passes (Modified), *1500 lbs</b> <b>Passes</b> <b>Passes</b> <b>Passes</b> <b>Passes, Class I</b> <b>&gt;0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes</b>	Ce Test Est Destiné À Comparer Les Propriétés Relatives De Différents Styles Et Constructions. Les Résultats Sont Basés Sur Un Test De Laboratoire Et Utilisés À Des Fins De Comparaison - La Limite De Charge Réelle Peut Varier.
Poinçonnement Rémanent (Astm F1914)		
Résistance À La Chaleur (Astm F1514)		
Résistance À La Lumière (Astm F1515)		
Résistance Chimique (Astm F925)		
Essai Au Panneau Radiant (Astm E648)		
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)		Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

- Limitée Commerciale De 15 Ans
- Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw’s diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Attributs + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Agréé
Climate Impact	
Environmental Product Declaration (EPD)	Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017
Embodied Carbon (Cradle to Gate)	6.05 Kg Co <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   Certifié Par Un Tiers
	Country of Origin   Imported

Contribution Au Certificat Vert Leed

« Crédit MR : Divulgateion et optimisation des produits de construction  
« Crédit MR : Divulgateion et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions
















[Installation Guidelines](#)  
[Maintenance Guidelines](#)

**Health Product Declaration (HPD) | 100 Ppm Disclosure**  
**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Conch Shell Oak 07140 LRV 31.4   L* 62.8 V3 - Moderate Variation	Heirloom Oak 07150 LRV 22.9   L* 54.92 V3 - Moderate Variation	Maize Wenge 07210 LRV 33.5   L* 64.52 V2 - Slight Variation	Wheat Oak 07220 LRV 32.6   L* 63.86 V3 - Moderate Variation	Tahini Oak 07240 LRV 27   L* 58.95 V3 - Moderate Variation	Caramel Wenge 07250 LRV 22.7   L* 54.73 V2 - Slight Variation
					
Cadmium Oak 07515 V3 - Moderate Variation	Anise Oak 07570 LRV 13.4   L* 43.36 V4 - Substantial Variation	Spiced Oak 07630 LRV 13.9   L* 44.11 V4 - Substantial Variation	Palomino Oak 07660 LRV 20.3   L* 52.14 V3 - Moderate Variation	Brushed Suede Oak 07700 LRV 13.4   L* 43.36 V4 - Substantial Variation	Allspice Walnut 07710 LRV 12.2   L* 41.53 V3 - Moderate Variation
					
Coriander Oak 07720 LRV 20.6   L* 52.5 V3 - Moderate Variation	Gabon Wenge 07730 LRV 10.9   L* 39.35 V2 - Slight Variation	Chocolate Walnut 07760 LRV 9.3   L* 36.48 V3 - Moderate Variation	Raw Umber Oak 07780 LRV 9.3   L* 36.58 V3 - Moderate Variation		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

