

Thoughtful

| | | |
|----------------------------|---|-------------------------|
| Coleção | Creating Space | |
| Número Do Produto | 4122V | |
| Construção | Heavy Commercial Luxury Vinyl Tile | |
| classe | Class III, Type B | |
| Acabamento | ExoGuard+® | |
| | U.s. | Metric |
| Dimensões Nominais | 24 in w x 24 in l | 60 cm w x 60 cm l |
| Dimensões Reais | 23.62 in w x 23.62 in l | 59.99 cm w x 59.99 cm l |
| Espessura Da Camada De Uso | 20 mil (0.02 in) | 0.51 mm |
| Espessura Total Do Produto | 0.197 in | 5 mm |
| Perfil De Borda | Borda Quadrada | |
| Instalação | Direct Glue | |
| Adesivo Recomendado | S150 Resilient Sheet Spray 1 Can, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 | |

Empacotamento

| | | |
|-----------------|-------------|-----------|
| Peças Por Caixa | 6 pcs | |
| Área Por Caixa | 23.25 sq ft | 2.16 sq m |
| Peso Por Caixa | 51.929 lbs | 23.55 kg |



Método De Instalação Recomendado



↑

↑

↑

↑

Monolithic

↑

↑

↑

↑

↑

Brick

↑

↑

↑

↑

↑

↑

Ashlar

Produtos Coordenados

LVT: Kind
Carpet Tile: Aware Tile, Conscious Tile, Intention Tile, Present Tile, Aware Ecologix® Tile

desempenho + teste

| | |
|---|---|
| recuo residual (ASTM F1914) | Passes |
| resistência ao calor (ASTM F1514) | Passes |
| resistência à luz (ASTM F1515) | Passes |
| resistência a produtos químicos (ASTM F925) | Passes |
| painel radiante (ASTM E648) | Passes, Class I |
| coeficiente de atrito (ASTM D2407, resistência ao deslizamento) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[Commercial 15 Year Underbed Bond Warranty](#)
[15 Anos Comercial Limitada](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Atributos + Certificações

| | |
|---|---|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Certificado |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 6.05 Kg CO ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | CE Marking (EN 14041) Certificado 3rd Party |
| | Country of Origin Imported |

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
 X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
 X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
 Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
 X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants
Ortho-Phthalates
FloorScore® Certificate

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção
 Ingredientes materiais - Opção 1: Relatório de ingredientes materiais
 MR Credit: Divulgação e otimização de produtos de construção
 Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)
 Crédito de EQ: Materiais de baixa emissão
 Opção 1: cálculos de categoria de produto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore® Certified

[Installation Guidelines](#)


[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
 Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
 *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways



Gesture 22100
V2 - Slight Variation



Vellum 22103
LRV 47.3 | L* 74.36
V2 - Slight Variation




Chalk 22111
V2 - Slight Variation




Jade 22405
V2 - Slight Variation




Indigo 22429
V2 - Slight Variation



Crisp 22518
V2 - Slight Variation



Warmth 22530
V2 - Slight Variation



Charcoal 22585
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

