

Terrain II Rigid Core


Collection	Terrain II	
Style Number	4125V	
class	Class III, Type B	
Finish	ExoGuard+®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 122 cm l
Actual Dimensions	7.00 in w x 48.00 in l	17.78 cm w x 121.92 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Product Thickness	0.157 in	4 mm
Edge Profile	Micro-Bevel	
Installation Type	InLine Level Edge	
Installation	Direct Glue	
Recommended Adhesive	, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , or 4151 Multi-Use Premium 4 Gallon	

Packaging

Area Per Box	27.96 sq ft	2.6 sq m
Weight Per Box	42.24 lbs	19.16 kg



Recommended Installation Method



Coordinating Products

LVT: Terrain II 12 Mil, Terrain II 20 Mil, Terrain II 30 Mil, Terrain II 20 Mil 5 Mm, Terrain II 12 Mil 2.0

performance + testing

residual indentation (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
radiant panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Warranties

- Commercial 15 Year Underbed Bond Warranty
- 15 Year Commercial Limited

Attributes + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	12.1 Kg CO ₂ /M ²
Total Recycled Content	20% (Pre-Consumer 20% Post-Consumer 0%)
Global Product Assessment	Environmental Guarantee* Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Shaw Manufactured Resilient Within The United States And Canada At No Cost to The Customer.
	CE Marking (EN 14041) 3rd Party Certified
	Country of Origin United States

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate
X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization – max 2 pts	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore® Certified

Additional Information

* To learn more about the recyclability of our products and our Environmental Guarantee, please visit shawcontract.com/sustainability.

Installation Guidelines



















Maintenance Guidelines










Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.


Available Colorways


 Willow 00170 V3 - Moderate Variation	 Thatch 00173 V2 - Slight Variation	 Ash 00174 V3 - Moderate Variation	 Saffron 00230 V2 - Slight Variation	 Trail 00256 V2 - Slight Variation	 Olive 00350 V2 - Slight Variation
 Spruce 00360 V2 - Slight Variation	 Aqua 00370 V2 - Slight Variation	 Azure 00400 V2 - Slight Variation	 Ink 00450 V2 - Slight Variation	 Slate 00540 V2 - Slight Variation	 Shade 00564 V2 - Slight Variation
 Root 00568 V4 - Substantial Variation	 Timber 00572 V2 - Slight Variation	 Graphite 00580 V2 - Slight Variation	 Terra 00600 V2 - Slight Variation	 Redwood 00650 V2 - Slight Variation	 Pirch 00684 V2 - Slight Variation


 Natural 00710 V2 - Slight Variation	 Lodge 00740 V2 - Slight Variation	 Grove 00769 V3 - Moderate Variation	 Nest 00774 V2 - Slight Variation	 Echo 00775 V2 - Slight Variation	 Cherry 00850 V2 - Slight Variation
 Violet 00965 V2 - Slight Variation	 Summit 05012 V3 - Moderate Variation	 Orchard 05013 V2 - Slight Variation	 Lark 05016 V3 - Moderate Variation	 Aspen 05019 V4 - Substantial Variation	 Sequoia 07003 V2 - Slight Variation
 Sumac 07004 V3 - Moderate Variation	 Alder 07005 V2 - Slight Variation	 Thicket 07008 V2 - Slight Variation			


Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1

Uniform Appearance

V2

Slight Variation

V3

Moderate Variation

V4

Substantial Variation