

Cover

Collection	<b>Cover + Envelop</b>	
Style Number	<b>4140V</b>	
class	<b>Class I, Type B</b>	
Finish	<b>ExoGuard+®</b>	
	U.s.	Metric
Nominal Dimensions	<b>7 in w x 48 in l</b>	<b>18 cm w x 122 cm l</b>
Actual Dimensions	<b>7.00 in w x 48.00 in l</b>	<b>17.78 cm w x 121.92 cm l</b>
Wear Layer Thickness	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Overall Product Thickness	<b>0.157 in</b>	<b>4 mm</b>
Edge Profile	<b>Micro-Bevel</b>	
Installation Type	<b>InLine Level Edge</b>	
Installation	<b>Direct Glue</b>	
Recommended Adhesive	<b>, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , or 4151 Multi-Use Premium 4 Gallon</b>	

Packaging

Area Per Box	<b>27.96 sq ft</b>	<b>2.6 sq m</b>
Weight Per Box	<b>42.24 lbs</b>	<b>19.16 kg</b>



Recommended Installation Method



performance + testing

residual indentation (ASTM F1914)	<b>Passes</b>
resistance to heat (ASTM F1514)	<b>Passes</b>
resistance to light (ASTM F1515)	<b>Passes</b>
resistance to chemicals (ASTM F925)	<b>Passes</b>
radiant panel (ASTM E648)	<b>Passes, Class I</b>
coefficient of friction (ASTM D2407, slip resistance)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranties

[Commercial 15 Year Underbed Bond Warranty](#)  
[15 Year Commercial Limited](#)

## Attributes + Certifications

## Health &amp; Wellbeing

Material Ingredient Transparency  
 Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
 FloorScore® | Certified

## Climate Impact

Environmental Product Declaration (EPD)  
 Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017  
 20% (Pre-Consumer 20% | Post-Consumer 0%)

## Global Product Assessment

Environmental Guarantee\* | Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Shaw Manufactured Resilient Within The United States And Canada At No Cost to The Customer.

CE Marking (EN 14041) | 3rd Party Certified  
 Country of Origin | United States

## WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition  
 X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt  
 X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt  
 Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt  
 X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt  
 X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization – max 2 pts

**Absence of Asbestos**  
**Absence of Heavy Metals**  
**Absence of Halogenated Flame Retardants**  
  
**Ortho-Phthalates**  
**FloorScore Certificate**  
**Health Product Declaration (HPD) | 1000 Ppm Disclosure**

## Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
 Material Ingredients - Option 1: Material Ingredient Reporting  
 MR Credit: Building Product Disclosure and Optimization  
 Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)  
 EQ Credit: Low Emitting Materials  
 Option 1: Product Category Calculations

**Health Product Declaration (HPD) | 100 Ppm Disclosure**  
  
**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore® Certified**

## Additional Information

\* To learn more about the recyclability of our products and our Environmental Guarantee, please visit [shawcontract.com/sustainability](http://shawcontract.com/sustainability).













[Installation Guidelines](#)[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
 Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
 \*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Shelter 00515 V2 - Slight Variation	Enclose 01031 V2 - Slight Variation	Uphold 01035 V2 - Slight Variation	Maintain 01040 V2 - Slight Variation	Support 02001 V3 - Moderate Variation	Surety 05057 V2 - Slight Variation
					
Retreat 05110 V2 - Slight Variation	Refuge 05111 V3 - Moderate Variation	Enshroud 06000 V3 - Moderate Variation	Resolve 07059 V4 - Substantial Variation	Preserve 07067 V2 - Slight Variation	Secure 07068 V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

