

Cover

Collection	Cover + Envelop	
Numéro De Style	4140V	
classe	Class I, Type B	
Finition	ExoGuard+®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensions Réelles	7.00 in w x 48.00 in l	17.78 cm w x 121.92 cm l
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.157 in	4 mm
Profil Du Bord	Micro-Biseau	
Installation Type	InLine Level Edge	
Installation	Direct Glue	
Adhésif Recommandé	, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , or 4151 Multi-Use Premium 4 Gallon	

Emballage

Surface Par Carton	27.96 sq ft	2.6 sq m
Poids Par Carton	42.24 lbs	19.16 kg



Méthodes d'Installation Conseillées



Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes
Essai Au Panneau Radiant (Astm E648)	Passes, Class I
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Garanties

[Limitée Commerciale De 15 Ans](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Attributs + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Agréé
Climate Impact	
Environmental Product Declaration (EPD)	Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017
Total Recycled Content	20% (Pre-Consumer 20%   Post-Consumer 0%)
Global Product Assessment	Environmental Guarantee*   Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Shaw Manufactured Resilient Within The United States And Canada At No Cost to The Customer.
	CE Marking (EN 14041)   Certifié Par Un Tiers
	Country of Origin   United States












Contribution Au Certificat Vert Leed

« Crédit MR : Divulgateion et optimisation des produits de construction	Health Product Declaration (HPD)   100 Ppm Disclosure
« Crédit MR : Divulgateion et optimisation des produits de construction	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédit EQ : matériaux faibles émissions	FloorScore Certified

Informations Supplémentaires

* To learn more about the recyclability of our products and our Environmental Guarantee, please visit <a href="#">shawcontract.com/sustainability</a> .	
<a href="#">Installation Guidelines</a>	Please visit <a href="#">www.shawcontract.com</a> for the most current warranty information.
<a href="#">Maintenance Guidelines</a>	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.
	Visit <a href="#">shawcontract.com/testing</a> for more information.

Available Colorways

					
Shelter 00515 V2 - Slight Variation	Enclose 01031 V2 - Slight Variation	Uphold 01035 V2 - Slight Variation	Maintain 01040 V2 - Slight Variation	Support 02001 V3 - Moderate Variation	Surety 05057 V2 - Slight Variation
					
Retreat 05110 V2 - Slight Variation	Refuge 05111 V3 - Moderate Variation	Enshroud 06000 V3 - Moderate Variation	Resolve 07059 V4 - Substantial Variation	Preserve 07067 V2 - Slight Variation	Secure 07068 V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

