

Cover

| | | |
|----------------------------|---|--------------------------|
| Coleção | Cover + Envelop | |
| Número Do Produto | 4140V | |
| classe | Class I, Type B | |
| Acabamento | ExoGuard+® | |
| | U.s. | Metric |
| Dimensões Nominais | 7 in w x 48 in l | 18 cm w x 122 cm l |
| Dimensões Reais | 7.00 in w x 48.00 in l | 17.78 cm w x 121.92 cm l |
| Espessura Da Camada De Uso | 20 mil (0.02 in) | 0.51 mm |
| Espessura Total Do Produto | 0.157 in | 4 mm |
| Perfil De Borda | Micro-Chanfrado | |
| Installation Type | InLine Level Edge | |
| Instalação | Direct Glue | |
| Adesivo Recomendado | , 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , or 4151 Multi-Use Premium 4 Gallon | |

Empacotamento

| | | |
|----------------|-------------|----------|
| Área Por Caixa | 27.96 sq ft | 2.6 sq m |
| Peso Por Caixa | 42.24 lbs | 19.16 kg |



Método De Instalação Recomendado



Desempenho + Teste

| | |
|---|---|
| Recuo Residual (Astm F1914) | Passes |
| Resistência Ao Calor (Astm F1514) | Passes |
| Resistência À Luz (Astm F1515) | Passes |
| Resistência A Produtos Químicos (Astm F925) | Passes |
| Painel Radiante (Astm E648) | Passes, Class I |
| Coeficiente De Atrito (Astm D2407, Resistência Ao Deslizamento) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Atributos + Certificações

| | |
|---|---|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Certificado |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017 |
| Total Recycled Content | 20% (Pre-Consumer 20% Post-Consumer 0%) |
| Global Product Assessment | Environmental Guarantee* Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Shaw Manufactured Resilient Within The United States And Canada At No Cost to The Customer. |
| | CE Marking (EN 14041) Certificado 3rd Party |
| | Country of Origin United States |












Crédito De Contribuição

| | |
|--|--|
| MR Credit: Divulgação e otimização de produtos de construção | Health Product Declaration (HPD) 100 Ppm Disclosure |
| Ingredientes materiais - Opção 1: Relatório de ingredientes materiais | |
| MR Credit: Divulgação e otimização de produtos de construção | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD) | FloorScore Certified |
| Crédito de EQ: Materiais de baixa emissão | |
| Opção 1: cálculos de categoria de produto | |

Informação Adicional

| | |
|---|--|
| * To learn more about the recyclability of our products and our Environmental Guarantee, please visit shawcontract.com/sustainability . | |
| Installation Guidelines | Please visit www.shawcontract.com for the most current warranty information. |
| Maintenance Guidelines | Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. |
| | This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. |
| | *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. |
| | Visit shawcontract.com/testing for more information. |

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Shelter 00515 V2 - Slight Variation | Enclose 01031 V2 - Slight Variation | Uphold 01035 V2 - Slight Variation | Maintain 01040 V2 - Slight Variation | Support 02001 V3 - Moderate Variation | Surety 05057 V2 - Slight Variation |
|  |  |  |  |  |  |
| Retreat 05110 V2 - Slight Variation | Refuge 05111 V3 - Moderate Variation | Enshroud 06000 V3 - Moderate Variation | Resolve 07059 V4 - Substantial Variation | Preserve 07067 V2 - Slight Variation | Secure 07068 V3 - Moderate Variation |

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

