

Stratum Nordic


Collection	Stratum	
Style Number	4073V	
Construction	Multilayer WPC With Attached Cork Underlayment	
class	Class III, Type B	
Attached Underlayment	Cork	
Finish	ExoGuard®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 122 cm l
Actual Dimensions	7.17 in w x 48.03 in l	18.21 cm w x 122.00 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Product Thickness	0.315 in	8 mm
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating Or Direct Glue	
Recommended Adhesive	, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or	

Packaging

Pieces Per Box	12 pcs	
Area Per Box	28.68 sq ft	2.66 sq m
Weight Per Box	48.59 lbs	22.04 kg



Recommended Installation Method



Coordinating Products

COREtec: Stratum XI, Stratum Eiris, Stratum Linear, Defined

performance + testing

residual indentation (ASTM F1914)	Passes
resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
radiant panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Attributes + Certifications

Climate Impact	
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	Greenguard (Certification, Gold, Private Label) Certified

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.

Available Colorways

					
Aspen 73100 V2 - Slight Variation	Natural 73101 V2 - Slight Variation	Honey 73103 V2 - Slight Variation	Alder 73104 V3 - Moderate Variation	Calm 73111 V2 - Slight Variation	Blonde 73112 V2 - Slight Variation
					
Driftwood 73120 V3 - Moderate Variation	Birch 73140 V2 - Slight Variation	Fir 73155 V2 - Slight Variation	Radiant 73710 V2 - Slight Variation	Redwood 73720 V2 - Slight Variation	Elm 73721 V2 - Slight Variation



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

