

Stratum Nordic


コレクション	Stratum	
スタイルナンバー	4073V	
建設	コルク下敷を含む多層WPC	
クラス	Class III, Type B	
付属下敷	コルク	
仕上げ	ExoGuard®	
	米国	メートル法
公称寸法	7 in w x 48 in l	18 cm w x 122 cm l
実際の寸法	7.17 in w x 48.03 in l	18.21 cm w x 122.00 cm l
摩耗層の厚さ	20 mil (0.02 in)	0.51 mm
製品全体の厚さ	0.315 in	8 mm
エッジプロファイル	マイクロベベル	
Installation Type	Click	
インストール	Floating Or Direct Glue	
推奨接着剤	, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or	

包装

ボックスあたりの個数	12 pcs	
ボックスあたりの面積	28.68 sq ft	2.66 sq m
ボックスあたりの重量	48.59 lbs	22.04 kg



推奨インストール方法



コーディネート商品

COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Eiris, Defined

パフォーマンス + テスト

残留圧痕 (ASTM F1914)	Passes
耐熱性 (ASTM F1514)	Passes
耐光性 (ASTM F1515)	Passes
耐薬品性 (ASTM F925)	Passes
放射パネル (ASTM E648)	Passes, Class I
摩擦係数(ASTM D2407、滑り抵抗)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

属性+認定

Climate Impact	
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin 中国

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	Greenguard (Certification, Gold, Private Label) Certified

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言（EPD）	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.

Available Colorways

 Aspen 73100 V2 - Slight Variation	 Natural 73101 V2 - Slight Variation	 Honey 73103 V2 - Slight Variation	 Alder 73104 V3 - Moderate Variation	 Calm 73111 V2 - Slight Variation	 Blonde 73112 V2 - Slight Variation
 Driftwood 73120 V3 - Moderate Variation	 Birch 73140 V2 - Slight Variation	 Fir 73155 V2 - Slight Variation	 Radiant 73710 V2 - Slight Variation	 Redwood 73720 V2 - Slight Variation	 Elm 73721 V2 - Slight Variation



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

