

## Stratum Nordic


수집	<b>Stratum</b>	
스타일 번호	<b>4073V</b>	
구성	<b>코르크제 바닥밀갈개가 부착된 다층 통계적 공정관리(WPC)</b>	
수업	<b>Class III, Type B</b>	
첨부 된 밀 갈개	<b>코르크</b>	
끝	<b>ExoGuard®</b>	
	미국	미터법
공칭 치수	<b>7 in w x 48 in l</b>	<b>18 cm w x 122 cm l</b>
실제 치수	<b>7.17 in w x 48.03 in l</b>	<b>18.21 cm w x 122.00 cm l</b>
마모 층 두께	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
전체 제품 두께	<b>0.315 in</b>	<b>8 mm</b>
가장자리 프로파일	<b>마이크로 베벨</b>	
Installation Type	<b>Click</b>	
설치	<b>Floating Or Direct Glue</b>	
권장 접착제	<b>, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or</b>	



### 포장

상자 당 조각	<b>12 pcs</b>	
상자 당 면적	<b>28.68 sq ft</b>	<b>2.66 sq m</b>
상자 당 무게	<b>48.59 lbs</b>	<b>22.04 kg</b>

### 권장 설치 방법



### 코디네이팅 제품

COREtec: Stratum 500, Stratum 700, Stratum XI, Stratum Eiris, Stratum Linear, Defined

### 공연 + 테스트

잔차 들어 쓰기 (ASTM F1914)	<b>Passes</b>
내열성 (ASTM F1514)	<b>Passes</b>
내광성 (ASTM F1515)	<b>Passes</b>
화학 물질에 대한 내성 (ASTM F925)	<b>Passes</b>
복사 패널 (ASTM E648)	<b>Passes, Class I</b>
마찰 계수 (ASTM D2407, 미끄러짐 저항)	<b>&gt;0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

속성 + 인증

Climate Impact	
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>Greenguard (Certification, Gold, Private Label)   Certified</b>

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축 환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Installation Guidelines	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.

Available Colorways

 Aspen 73100 V2 - Slight Variation	 Natural 73101 V2 - Slight Variation	 Honey 73103 V2 - Slight Variation	 Alder 73104 V3 - Moderate Variation	 Calm 73111 V2 - Slight Variation	 Blonde 73112 V2 - Slight Variation
 Driftwood 73120 V3 - Moderate Variation	 Birch 73140 V2 - Slight Variation	 Fir 73155 V2 - Slight Variation	 Radiant 73710 V2 - Slight Variation	 Redwood 73720 V2 - Slight Variation	 Elm 73721 V2 - Slight Variation



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

