

Stratum Nordic


|                           |  |                          |
|---------------------------|--|--------------------------|
| Collection                | Stratum  |                          |
| Style Number              | 4073V  |                          |
| Construction              | Multilayer WPC With Attached Cork Underlayment |                          |
| class                     | Class III, Type B                              |                          |
| Attached Underlayment     | Cork   |                          |
| Finish                    | ExoGuard®                                      |                          |
|                           | U.s.   | Metric                   |
| Nominal Dimensions        | 7 in w x 48 in l                               | 18 cm w x 122 cm l       |
| Actual Dimensions         | 7.17 in w x 48.03 in l                         | 18.21 cm w x 122.00 cm l |
| Wear Layer Thickness      | 20 mil (0.02 in)                               | 0.51 mm                  |
| Overall Product Thickness | 0.315 in                                       | 8 mm                     |
| Edge Profile              | Micro-Bevel                                    |                          |
| Installation Type         | Click  |                          |
| Installation              | Floating Or Direct Glue                        |                          |
| Recommended Adhesive      | 2200 Resilient Tile 4 Gallon                   |                          |

Packaging

|                |             |           |
|----------------|-------------|-----------|
| Pieces Per Box | 12 pcs      |           |
| Area Per Box   | 28.68 sq ft | 2.66 sq m |
| Weight Per Box | 48.59 lbs   | 22.04 kg  |



Recommended Installation Method



Coordinating Products

COREtec: Stratum XI, Stratum Eiris, Stratum Linear, Defined

Performance + Testing

|   |   |
|---|---|
| Residual Indentation (Astm F1914)                     | Passes  |
| Resistance To Heat (Astm F1514)                       | Passes  |
| Resistance To Light (Astm F1515)                      | Passes  |
| Resistance To Chemicals (Astm F925)                   | Passes  |
| Coefficient Of Friction (Astm D2407, Slip Resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Attributes + Certifications

Climate Impact

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Greenguard (Certification, Gold, Private Label) | Certified

Country of Origin | China

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)  
EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017  
Greenguard Gold Certified

Installation Guidelines

Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

|  |   |   |  |   |   |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Aspen 73100<br>V2 - Slight Variation   | Natural 73101<br>V2 - Slight Variation  | Honey 73103<br>V2 - Slight Variation  | Alder 73104<br>V3 - Moderate Variation   | Calm 73111<br>V2 - Slight Variation   | Blonde 73112<br>V2 - Slight Variation   |
|  |  |  |  |  |  |
| Driftwood 73120<br>V3 - Moderate Variation   | Birch 73140<br>V2 - Slight Variation  | Fir 73155<br>V2 - Slight Variation  | Radiant 73710<br>V2 - Slight Variation   | Redwood 73720<br>V2 - Slight Variation  | Elm 73721<br>V2 - Slight Variation  |



Balance 73755      Golden 73756  
V2 - Slight Variation      V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

