


Expression

|                            |  |                          |
|----------------------------|--|--------------------------|
| Colección                  | Community  |                          |
| Número De Estilo           | 4069V  |                          |
| Construcción               | SPC Multicapa Con Base De Corcho Adjunta   |                          |
| clase                      | Class III, Type B  |                          |
| Manta Inferior Adicional   | Corcho   |                          |
| Terminación                | ExoGuard®  |                          |
|                            | U.s.   | Metric                   |
| Dimensiones Nominales      | 7 in w x 48 in l   | 18 cm w x 122 cm l       |
| Dimensiones Reales         | 7.17 in w x 48.03 in l   | 18.21 cm w x 122.00 cm l |
| Desgaste De La Capa De Uso | 20 mil (0.02 in)   | 0.51 mm                  |
| Espesor Total Del Producto | 0.217 in   | 5.5 mm                   |
| Perfil De Borde            | Micro-Biselado   |                          |
| Installation Type          | Click  |                          |
| Instalación                | Floating Or Direct Glue  |                          |
| Adhesivo Recomendado       | , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon |                          |

Embalaje

|                 |             |           |
|-----------------|-------------|-----------|
| Piezas Por Caja | 12 pcs      |           |
| Área Por Caja   | 28.68 sq ft | 2.66 sq m |
| Peso Por Caja   | 48.41 lbs   | 21.96 kg  |

Método De Instalación Recomendado



Productos Que Combinan

COREtec: Inclusive

Carpet Tile: Knotted Tile, Process Tile, Back Weave Tile, Exchange Tile, Heddle Tile, Flat Weave Tile

Broadloom: Embrace, Share



Desempeño + Pruebas

|  |   |
|--|---|
| Resistencia Al Calor (Astm F1514)  | Passes  |
| Resistencia A La Luz (Astm F1515)  | Passes  |
| Resistencia A Productos Químicos (Astm F925)   | Passes  |
| Panel Radiante (Astm E648)   | Passes, Class I   |
| Coefficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento)  | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. |   |

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

|   |   |
|---|---|
| Health & Wellbeing                      |   |
| Material Ingredient Transparency        | Health Product Declaration (HPD)   1000 ppm Disclosure                                |
| Indoor Air Quality                      | FloorScore®   Certificado   |
| Climate Impact                          |   |
| Environmental Product Declaration (EPD) | Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017 |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)   |
| Global Product Assessment               | Country of Origin   China   |

Contribución Para Créditos Leed

|  |  |
|--|--|
| Crédito MR: Divulgación y optimización de productos de construcción<br>Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017   |
| Crédito EQ: Materiales de baja emisión<br>Opción 1: Cálculos de categoría de producto  | FloorScore Certified   |
| Installation Guidelines  | Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.<br>Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.<br><br>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.<br>*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.<br><br>Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information. |
| Maintenance Guidelines   |  |

Available Colorways

