


Inclusive

Colección	Community	
Número De Estilo	4068V	
Construcción	SPC Multicapa Con Base De Corcho Adjunta	
clase	Class III, Type B	
Manta Inferior Adicional	Corcho	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensiones Reales	7.17 in w x 48.03 in l	18.21 cm w x 122.00 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.217 in	5.5 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating Or Direct Glue	
Adhesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Piezas Por Caja	12 pcs	
Área Por Caja	28.68 sq ft	2.66 sq m
Peso Por Caja	48.41 lbs	21.96 kg

Método De Instalación Recomendado



Productos Que Combinan

COREtec: Expression
Carpet Tile: Knotted Tile, Process Tile, Back Weave Tile, Exchange Tile, Heddle Tile, Flat Weave Tile
Broadloom: Embrace, Share



Desempeño + Pruebas

Dimensional Stability (ASTM F2199)	Passes
Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Resistencia A Productos Químicos (Astm F925)	Passes
Panel Radiante (Astm E648)	Passes, Class I
Coeficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin China

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. Visit shawcontract.com/testing for more information.
Maintenance Guidelines	

Available Colorways



Sterling 68111
V2 - Slight Variation



Moonlit 68120
V2 - Slight Variation



Hazy 68122
V2 - Slight Variation



Washed 68125
V2 - Slight Variation



Copperwood 68210
V2 - Slight Variation



Gunmetal 68516
V2 - Slight Variation



Industrial 68599
V2 - Slight Variation



Champagne 68705
V2 - Slight Variation



Brownstone 68710
V2 - Slight Variation



Caraway 68720
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

