


Inclusive

系列	Community	
款型编号	4068V	
结构	软木底多层复合	
类型	Class III, Type B	
附加垫层	软木	
表面处理	ExoGuard®	
	美国	尺寸标准
公称尺寸	7 in w x 48 in l	18 cm w x 122 cm l
实际尺寸	7.17 in w x 48.03 in l	18.21 cm w x 122.00 cm l
耐磨层厚度	20 mil (0.02 in)	0.51 mm
产品整体厚度	0.217 in	5.5 mm
边缘轮廓	微斜角	
Installation Type	Click	
安装方式	Floating Or Direct Glue	
胶粘剂建议	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

包装

每盒件数	12 pcs	
每箱面积	28.68 sq ft	2.66 sq m
每箱重量	48.41 lbs	21.96 kg

铺装建议



搭配产品

COREtec: Expression  
Carpet Tile: Knotted Tile, Process Tile, Back Weave Tile, Exchange Tile, Heddle Tile, Flat Weave Tile



性能 + 测试

Dimensional Stability (ASTM F2199)	Passes
耐热性 (ASTM F1514)	Passes
耐光性 (ASTM F1515)	Passes
耐化学性 (ASTM F925)	Passes
辐射板 (ASTM E648)	Passes, Class I
摩擦系数 (ASTM D2407, 防滑性)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

质保

15年商用有限质保

属性+认证

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   认证
Climate Impact	
Environmental Product Declaration (EPD)	通过ISO 14025、EN 15804和ISO 21930 : 2017等第三方认证
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   中国

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	Greenguard Gold Certificate

绿色leed贡献信用

MR Credit : 建立产品披露和优化	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
环境产品声明-选项1：环境产品声明 (EPD)	FloorScore® Certified
EQ信用：低排放材料	
选项1：产品类别计算	
Installation Guidelines	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Sterling 68111  
V2 - Slight Variation



Moonlit 68120  
V2 - Slight Variation



Hazy 68122  
V2 - Slight Variation



Washed 68125  
V2 - Slight Variation



Copperwood 68210  
V2 - Slight Variation



Gunmetal 68516  
V2 - Slight Variation



Industrial 68599  
V2 - Slight Variation



Champagne 68705  
V2 - Slight Variation



Brownstone 68710  
V2 - Slight Variation



Caraway 68720  
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

