

Inclusive


|                       |   |                          |
|-----------------------|---|--------------------------|
| Collection            | Community   |                          |
| Style Number          | 4068V   |                          |
| Construction          | Multilayer SPC With Attached Cork Underlayment  |                          |
| Class / ASTM F3261    | Class III, Type B   |                          |
| Attached Underlayment | Cork  |                          |
| Finish                | ExoGuard®   |                          |
|                       | U.s.  | Metric                   |
| Nominal Dimensions    | 7 in w x 48 in l  | 18 cm w x 122 cm l       |
| Actual Dimensions     | 7.17 in w x 48.03 in l  | 18.21 cm w x 122.00 cm l |
| Wear Layer Thickness  | 20 mil (0.02 in)  | 0.51 mm                  |
| Overall Thickness     | 0.217 in  | 5.5 mm                   |
| Edge Profile          | Micro-Bevel   |                          |
| Installation Type     | Click   |                          |
| Installation          | Floating Or Direct Glue   |                          |
| Recommended Adhesive  | 4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon |                          |

Packaging

|                   |             |           |
|-------------------|-------------|-----------|
| Pieces Per Carton | 12 pcs      |           |
| Area Per Carton   | 28.68 sq ft | 2.66 sq m |
| Weight Per Carton | 48.41 lbs   | 21.96 kg  |



Recommended Installation Method



Coordinating Products

- COREtec: Expression
- Carpet Tile: Knotted Tile, Process Tile, Back Weave Tile, Exchange Tile, Heddle Tile, Flat Weave Tile
- Broadloom: Embrace, Share

Performance + Testing

|  |   |
|--|---|
| Dimensional Stability (ASTM F2199)   | Passes  |
| Resistance To Heat (Astm F1514)  | Passes  |
| Resistance To Light (Astm F1515)   | Passes  |
| Resistance To Chemicals (Astm F925)  | Passes  |
| Coefficient Of Friction (Astm D2407, Slip Resistance)  | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. |   |

Warranties

15 Year Commercial Limited

Material Health & Environmental Certifications

|   |  |
|---|--|
| Health & Wellbeing                      |  |
| Material Ingredient Transparency        | Health Product Declaration (HPD)   1000 ppm Disclosure                       |
| Climate Impact                          |  |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)                                      |
| Global Product Assessment               | FloorScore®   Certified<br>Country of Origin   China                         |

Green Leed Contribution Credit

|   |  |
|---|--|
| MR Credit: Building Product Disclosure and Optimization<br>Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017   |
| EQ Credit: Low Emitting Materials<br>Option 1: Product Category Calculations  | FloorScore Certified   |
| Installation Guidelines   | Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.<br>Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.<br><br>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.<br>*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.<br><br>Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information. |
| Maintenance Guidelines  |  |

Available Colorways



Sterling 68111  
V2 - Slight Variation



Moonlit 68120  
V2 - Slight Variation



Hazy 68122  
V2 - Slight Variation



Washed 68125  
V2 - Slight Variation



Copperwood 68210  
V2 - Slight Variation



Gunmetal 68516  
V2 - Slight Variation



Industrial 68599  
V2 - Slight Variation



Champagne 68705  
V2 - Slight Variation



Brownstone 68710  
V2 - Slight Variation



Caraway 68720  
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

