

Respite

| | | |
|---------------------------|--|--------------------------|
| Style Number | 4090V | |
| Construction | Multilayer SPC With Attached Cork Underlayment | |
| class | Class III, Type B | |
| Attached Underlayment | Cork | |
| Finish | ExoGuard® | |
| | U.s. | Metric |
| Nominal Dimensions | 7 in w x 48 in l | 18 cm w x 122 cm l |
| Actual Dimensions | 7.20 in w x 48.03 in l | 18.29 cm w x 122.00 cm l |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Product Thickness | 0.197 in | 5 mm |
| Edge Profile | Micro-Bevel | |
| Installation Type | Click | |
| Installation | Floating Or Direct Glue | |
| Recommended Adhesive | , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL | |



Packaging

| | | |
|----------------|-------------|-----------|
| Pieces Per Box | 12 pcs | |
| Area Per Box | 28.84 sq ft | 2.68 sq m |
| Weight Per Box | 48.61 lbs | 22.05 kg |

Recommended Installation Method



performance + testing

| | |
|---|---|
| residual indentation (ASTM F1914) | Passes |
| resistance to heat (ASTM F1514) | Passes |
| resistance to light (ASTM F1515) | Passes |
| resistance to chemicals (ASTM F925) | Passes |
| radiant panel (ASTM E648) | Passes, Class I |
| coefficient of friction (ASTM D2407, slip resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Attributes + Certifications

| | |
|---|--|
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 20.5 Kg Co ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | Country of Origin Imported |

WELL V2 Contribution Credit

| | |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | Absence of Halogenated Flame Retardants |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt | Ortho-Phthalates |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt | Greenguard Gold Certificate |

Green Leed Contribution Credit

| | |
|--|--|
| MR Credit: Building Product Disclosure and Optimization | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | |
| Installation Guidelines | Please visit www.shawcontract.com for the most current warranty information. |
| Maintenance Guidelines | Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. |
| | This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. |
| | Visit shawcontract.com/testing for more information. |

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Path 90250 V2 - Slight Variation | Cabin 90506 V2 - Slight Variation | Alabaster 90515 V2 - Slight Variation | Ashen 90516 V2 - Slight Variation | Track 90710 V2 - Slight Variation | Lodge 90720 V4 - Substantial Variation |
|  |  |  |  | | |
| Cane 90740 V2 - Slight Variation | Glen 90750 V2 - Slight Variation | Trail 90760 V3 - Moderate Variation | Redwood 90840 V3 - Moderate Variation | | |

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

