

Respite


| | | |
|-----------------------|--|--------------------------|
| Style Number | 4090V | |
| Construction | Multilayer SPC With Attached Cork Underlayment | |
| Class / ASTM F3261 | Class III, Type B | |
| Attached Underlayment | Cork | |
| Finish | ExoGuard® | |
| | U.S. | Metric |
| Nominal Dimensions | 7 in w x 48 in l | 18 cm w x 122 cm l |
| Actual Dimensions | 7.20 in w x 48.03 in l | 18.29 cm w x 122.00 cm l |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Thickness | 0.197 in | 5 mm |
| Edge Profile | Micro-Bevel | |
| Installation Type | Click | |
| Installation | Floating Or Direct Glue | |
| Recommended Adhesive | , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL | |

Packaging

| | | |
|-------------------|-------------|-----------|
| Pieces per Carton | 12 pcs | |
| Area per Carton | 28.84 sq ft | 2.68 sq m |
| Weight per Carton | 48.61 lbs | 22.05 kg |



Recommended Installation Method



Performance + Testing

| | | |
|---|---|--|
| Static Load (ASTM F970) | Passes (Modified), *500 lbs | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |
| Residual Indentation (ASTM F1914) | Passes | |
| Resistance to Heat (ASTM F1514) | Passes | |
| Resistance to Light (ASTM F1515) | Passes | |
| Resistance to Chemicals (ASTM F925) | Passes | |
| Radiant Panel (ASTM E648) | Passes, Class I | |
| Coefficient of Friction (ASTM D2047, Slip Resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes | |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

Climate Impact

| | |
|---|--|
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 20.5 Kg Co ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

| | |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization | Absence of Halogenated Flame Retardants |
| X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization | Ortho-Phthalates |
| X11 Long Term Emissions Control Part 2: Flooring Optimization | Greenguard Gold Certificate |

Leed v4 Contribution Credits

| | |
|---|---|
| MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
|---|---|

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways



Path 90250
V2 - Slight Variation



Cabin 90506
V2 - Slight Variation



Alabaster 90515
V2 - Slight Variation



Ashen 90516
V2 - Slight Variation



Track 90710
V2 - Slight Variation



Lodge 90720
V4 - Substantial Variation



Cane 90740
V2 - Slight Variation



Glen 90750
V2 - Slight Variation



Trail 90760
V3 - Moderate Variation



Redwood 90840
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

