

## Respite


스타일 번호	4090V	
구성	코르크제 바닥밀갈개가 부착된 다층 통계적 공정관리(SPC)	
수업	Class III, Type B	
첨부 된 밀 갈개	코르크	
끝	ExoGuard®	
	미국	미터법
공칭 치수	7 in w x 48 in l	18 cm w x 122 cm l
실제 치수	7.20 in w x 48.03 in l	18.29 cm w x 122.00 cm l
마모 층 두께	20 mil (0.02 in)	0.51 mm
전체 제품 두께	0.197 in	5 mm
가장자리 프로파일	마이크로 베벨	
Installation Type	Click	
설치	Floating Or Direct Glue	
권장 접착제	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	



### 포장

상자 당 조각	12 pcs	
상자 당 면적	28.84 sq ft	2.68 sq m
상자 당 무게	48.61 lbs	22.05 kg

### 권장 설치 방법



### 공연 + 테스트

잔차 들어 쓰기 (ASTM F1914)	Passes
내열성 (ASTM F1514)	Passes
내광성 (ASTM F1515)	Passes
화학 물질에 대한 내성 (ASTM F925)	Passes
복사 패널 (ASTM E648)	Passes, Class I
마찰 계수(ASTM D2407, 미끄러짐 저항)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

### 보증

[15년 상용 제한](#)

속성 + 인증

Climate Impact

Environmental Product Declaration (EPD)  
Embodied Carbon (Cradle to Gate)  
Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득  
20.5 Kg Co<sub>2</sub>/M<sup>2</sup>  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition  
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt  
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt  
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos  
Absence of Heavy Metals  
Absence of Halogenated Flame Retardants  
  
Ortho-Phthalates  
Greenguard Gold Certificate

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축  
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
  
Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Path 90250  
V2 - Slight Variation



Cabin 90506  
V2 - Slight Variation



Alabaster 90515  
V2 - Slight Variation



Ashen 90516  
V2 - Slight Variation



Track 90710  
V2 - Slight Variation



Lodge 90720  
V4 - Substantial Variation



Cane 90740  
V2 - Slight Variation



Glen 90750  
V2 - Slight Variation



Trail 90760  
V3 - Moderate Variation



Redwood 90840  
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

