

Respite


款型编号	4090V	
结构	软木底多层复合	
类型	Class III, Type B	
附加垫层	软木	
表面处理	ExoGuard®	
	美国	尺寸标准
公称尺寸	7 in w x 48 in l	18 cm w x 122 cm l
实际尺寸	7.20 in w x 48.03 in l	18.29 cm w x 122.00 cm l
耐磨层厚度	20 mil (0.02 in)	0.51 mm
产品整体厚度	0.197 in	5 mm
边缘轮廓	微斜角	
Installation Type	Click	
安装方式	Floating Or Direct Glue	
胶粘剂建议	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

包装

每盒件数	12 pcs	
每箱面积	28.84 sq ft	2.68 sq m
每箱重量	48.61 lbs	22.05 kg



铺装建议



性能 + 测试

残余压痕 (ASTM F1914)	Passes
耐热性 (ASTM F1514)	Passes
耐光性 (ASTM F1515)	Passes
耐化学性 (ASTM F925)	Passes
辐射板 (ASTM E648)	Passes, Class I
摩擦系数 (ASTM D2407, 防滑性)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

属性+认证

Climate Impact	
Environmental Product Declaration (EPD)	通过ISO 14025、EN 15804和ISO 21930 : 2017等第三方认证
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	Greenguard Gold Certificate

绿色leed贡献信用

MR Credit : 建立产品披露和优化 环境产品声明-选项1：环境产品声明 (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Path 90250 V2 - Slight Variation	Cabin 90506 V2 - Slight Variation	Alabaster 90515 V2 - Slight Variation	Ashen 90516 V2 - Slight Variation	Track 90710 V2 - Slight Variation	Lodge 90720 V4 - Substantial Variation
					
Cane 90740 V2 - Slight Variation	Glen 90750 V2 - Slight Variation	Trail 90760 V3 - Moderate Variation	Redwood 90840 V3 - Moderate Variation		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

