

Respite


款型编号	4090V	
结构	软木底多层复合	
类型	Class III, Type B	
附加垫层	软木	
表面处理	ExoGuard®	
	美国	尺寸标准
公称尺寸	7 in w x 48 in l	18 cm w x 122 cm l
实际尺寸	7.20 in w x 48.03 in l	18.29 cm w x 122.00 cm l
耐磨层厚度	20 mil (0.02 in)	0.51 mm
产品整体厚度	0.197 in	5 mm
边缘轮廓	微斜角	
Installation Type	Click	
安装方式	Floating Or Direct Glue	
胶粘剂建议	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

包装

每盒件数	12 pcs	
每箱面积	28.84 sq ft	2.68 sq m
每箱重量	48.61 lbs	22.05 kg



铺装建议



性能 + 测试

残余压痕 (astm F1914)	Passes
耐热性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐化学性 (astm F925)	Passes
辐射板 (astm E648)	Passes, Class I
摩擦系数 (Astm D2407, 防滑性)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

质保

15年商用有限质保

属性+认证

Climate Impact

Environmental Product Declaration (EPD)  
Total Recycled Content

通过ISO 14025、EN 15804和ISO 21930 : 2017等第三方认证  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

绿色leed贡献信用

MR Credit : 建立产品披露和优化  
环境产品声明-选项1 : 环境产品声明 (EPD)

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Path 90250  
V2 - Slight Variation



Cabin 90506  
V2 - Slight Variation



Alabaster 90515  
V2 - Slight Variation



Ashen 90516  
V2 - Slight Variation



Track 90710  
V2 - Slight Variation



Lodge 90720  
V4 - Substantial Variation



Cane 90740  
V2 - Slight Variation



Glen 90750  
V2 - Slight Variation



Trail 90760  
V3 - Moderate Variation



Redwood 90840  
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.



