

Reside 12 Mil


Collection	Reside	
Numéro De Style	4094V	
Construction	Carreau De Vinyle De Luxe Commercial Léger	
classe		
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	6 in w x 47 in l	15 cm w x 120 cm l
Dimensions Réelles	5.91 in w x 47.24 in l	15.01 cm w x 119.99 cm l
Épaisseur De La Couche d'Usure	12 mil (0.012 in)	0.3 mm
Épaisseur Générale Du Produit	0.079 in	2 mm
Profil Du Bord	Bord Carré	
Installation Type	Dry Back	
Installation	Direct Glue	
Approved Spaces	Light Commercial	
Adhésif Recommandé	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or 4151 Multi-Use Premium 4 Gallon	



Emballage

Pièces Par Carton	27 pcs	
Surface Par Carton	52.3 sq ft	4.86 sq m
Poids Par Carton	40 lbs	18.14 kg

Méthodes d'Installation Conseillées



Coordination Des Produits

LVT: Reside 8 Mil, Reside 6 Mil, Reside 20 Mil

performance + Tests et essai

charge statique (ASTM F970)
poinçonnement rémanent (ASTM F1914)
résistance à la chaleur (ASTM F1514)
résistance à la lumière (ASTM F1515)
Essai au panneau radiant (Astm E648)
coefficient de frottement (ASTM D2407,
résistance au glissement)

Passes (Modified), *1500 lbs
Passes
Passes
Passes
Passes, Class I
≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[7 Year Light Commercial Limited Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Agréé

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)
Life-Cycle Carbon Emissions
Total Recycled Content

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025,
EN 15804 Et ISO 21930:2017
6.05 Kg CO₂/M²
Low Embodied Carbon
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Réduction des matières dangereuses Partie 1 : Optimisation des limites des matières dangereuses – 1 pt
X10 Réduction des composés volatils Partie 1 (A) : Gérer l'optimisation des composés organiques volatils (COV) - 1 pt
Partie 2 : Gérer l'optimisation des composés organiques semi-volatils (COSV) - 1 pt
X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt

Absence of Asbestos
Absence of Heavy Metals

Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Contribution Au Certificat Vert Leed

« Crédit MR : Divulcation et optimisation des produits de construction
« Crédit MR : Divulcation et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure
3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

