

Cast 2.5 Mm

|                           |  |                         |
|---------------------------|--|-------------------------|
| Collection                | Compound + Cast  |                         |
| Style Number              | 4097V  |                         |
| Construction              | Heavy Commercial Luxury Vinyl Tile   |                         |
| class                     | Class III, Type B  |                         |
| Finish                    | ExoGuard+®   |                         |
|                           | U.s.   | Metric                  |
| Nominal Dimensions        | 24 in w x 24 in l  | 61 cm w x 61 cm l       |
| Actual Dimensions         | 24.00 in w x 24.00 in l  | 60.96 cm w x 60.96 cm l |
| Wear Layer Thickness      | 20 mil (0.02 in)   | 0.51 mm                 |
| Overall Product Thickness | 0.098 in   | 2.5 mm                  |
| Edge Profile              | Squared Edge   |                         |
| Installation              | Direct Glue  |                         |
| Recommended Adhesive      | S150-95 Resilient Tile Spray, , 4200 Resilient Tile 4 Gallon, 2200 Simi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon |                         |

Packaging

|                |           |           |
|----------------|-----------|-----------|
| Pieces Per Box | 17 pcs    |           |
| Area Per Box   | 68 sq ft  | 6.32 sq m |
| Weight Per Box | 57.79 lbs | 26.21 kg  |



Recommended Installation Method



Coordinating Products

LVT: Compound 2.5 Mm, Compound 5.0, Cast 5.0 Mm

Performance + Testing

|                                     |        |
|-------------------------------------|--------|
| Residual Indentation (Astm F1914)   | Passes |
| Resistance To Heat (Astm F1514)     | Passes |
| Resistance To Light (Astm F1515)    | Passes |
| Resistance To Chemicals (Astm F925) | Passes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited  
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Attributes + Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Total Recycled Content

30% (Pre-Consumer 30% | Post-Consumer 0%)

Global Product Assessment

Environmental Guarantee\* | Through Our Environmental Guarantee, Shaw Pledges to Transport And Recycle Any Shaw Manufactured Resilient Within The United States And Canada At No Cost to The Customer.

FloorScore® | Certified

CE Marking (EN 14041) | 3rd Party Certified

Country of Origin | United States

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Additional Information

\* To learn more about the recyclability of our products and our Environmental Guarantee, please visit [shawcontract.com/sustainability](#).

Installation Guidelines

Maintenance Guidelines

Please visit [www.shawcontract.com](#) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](#) for more information.

Available Colorways



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

