

Repose

| | | |
|----------------------------|--|--------------------------|
| Colección | Living Environments | |
| Número De Estilo | 4089V | |
| Construcción | SPC Multicapa Con Base De Corcho Adjunta | |
| clase | | |
| Manta Inferior Adicional | Corcho | |
| Terminación | ExoGuard® | |
| | U.s. | Metric |
| Dimensiones Nominales | 7 in w x 48 in l | 18 cm w x 122 cm l |
| Dimensiones Reales | 7.13 in w x 48.03 in l | 18.11 cm w x 122.00 cm l |
| Desgaste De La Capa De Uso | 12 mil (0.012 in) | 0.3 mm |
| Espesor Total Del Producto | 0.173 in | 4.4 mm |
| Perfil De Borde | Micro-Biselado | |
| Installation Type | Click | |
| Instalación | Floating Or Direct Glue | |
| Adhesivo Recomendado | , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL | |

Embalaje

| | | |
|-----------------|-------------|-----------|
| Piezas Por Caja | 12 pcs | |
| Área Por Caja | 28.52 sq ft | 2.65 sq m |
| Peso Por Caja | 41.89 lbs | 19 kg |

Método De Instalación Recomendado



Productos Que Combinan

Sheet: Adventure Sheet

Broadloom: Scenery, Reimagine, Statement, Upscale, Imagery, Sentiment

Desempeño + Pruebas

| | |
|--|---|
| Margen Adicional Residual (Astm F1914) | Passes |
| Resistencia Al Calor (Astm F1514) | Passes |
| Resistencia A La Luz (Astm F1515) | Passes |
| Resistencia A Productos Químicos (Astm F925) | Passes |
| Densidad De Humo (Astm E662, Modo Flameado) | Passes |
| Panel Radiante (Astm E648) | Passes, Class I |
| Coefficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |
| Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number. | |

Garantías

10 Años Limitado A Uso Comercial

Atributos + Certificaciones

| | |
|---|---|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Certificado |
| Climate Impact | |
| Environmental Product Declaration (EPD) | Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017 |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | Country of Origin Imported |

Contribución Para Créditos Leed

| | |
|--|--|
| Crédito MR: Divulgación y optimización de productos de construcción Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales | Health Product Declaration (HPD) 100 Ppm Disclosure |
| Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto | FloorScore Certified |

Installation Guidelines
Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways



Canoe 89103
V3 - Moderate Variation



Cape 89111
V2 - Slight Variation



Shore 89114
V3 - Moderate Variation



Bare 89120
V2 - Slight Variation



Shell 89250
V3 - Moderate Variation



Tide 89506
V2 - Slight Variation



Adrift 89516
V2 - Slight Variation



Estuary 89684
V4 - Substantial Variation



Elk 89710
V2 - Slight Variation



Fauna 89720
V3 - Moderate Variation



Pike 89760
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation