

Branching Out Coretec 20 Mil


|                           |   |                          |
|---------------------------|---|--------------------------|
| Collection                | Branching Out   |                          |
| Style Number              | 4309V   |                          |
| class                     | Class III, Type B   |                          |
| Attached Underlayment     | Pad   |                          |
| Finish                    | ExoGuard+®  |                          |
|                           | U.s.  | Metric                   |
| Nominal Dimensions        | 7 in w x 48 in l  | 18 cm w x 122 cm l       |
| Actual Dimensions         | 6.92 in w x 48.03 in l  | 17.58 cm w x 122.00 cm l |
| Wear Layer Thickness      | 20 mil (0.02 in)  | 0.51 mm                  |
| Overall Product Thickness | 0.217 in  | 5.5 mm                   |
| Edge Profile              | Micro-Bevel   |                          |
| Installation Type         | Click   |                          |
| Installation              | Floating Or Direct Glue   |                          |
| Recommended Adhesive      | , 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon |                          |

Packaging

|                |             |           |
|----------------|-------------|-----------|
| Pieces Per Box | 10 pcs      |           |
| Area Per Box   | 23.11 sq ft | 2.15 sq m |
| Weight Per Box | 43.66 lbs   | 19.8 kg   |



Recommended Installation Method



Coordinating Products

COREtec: Branching Out Coretec 12 Mil, Branching Out WPC

performance + testing

|                                   |                 |
|-----------------------------------|-----------------|
| residual indentation (ASTM F1914) | Passes          |
| resistance to heat (ASTM F1514)   | Passes          |
| resistance to light (ASTM F1515)  | Passes          |
| radiant panel (ASTM E648)         | Passes, Class I |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)

Attributes + Certifications

|   |  |
|---|--|
| Health & Wellbeing                      |  |
| Indoor Air Quality                      | FloorScore®   Certified  |
| Climate Impact                          |  |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate)        | 20.5 Kg Co <sub>2</sub> /M <sup>2</sup>                                      |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)                                      |
| Global Product Assessment               | Country of Origin   China  |

WELL V2 Contribution Credit

|  |  |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition                         | <b>Absence of Asbestos</b>                     |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt                   | <b>Absence of Heavy Metals</b>                 |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | <b>Absence of Halogenated Flame Retardants</b> |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt                               | <b>Ortho-Phthalates</b>                        |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt                                     | <b>FloorScore Certificate</b>                  |

Green Leed Contribution Credit

|  |   |
|--|---|
| MR Credit: Building Product Disclosure and Optimization                                | <b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b> |
| Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | <b>FloorScore® Certified</b>  |
| EQ Credit: Low Emitting Materials  |   |
| Option 1: Product Category Calculations  |   |

[Installation Guidelines](#)

[Maintenance Guidelines](#)


Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways


|  |   |   |  |   |   |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Alpine Oak 56100<br>V3 - Moderate Variation  | Zion Oak 56103<br>V2 - Slight Variation   | Rise Oak 56120<br>V3 - Moderate Variation   | Riverside Oak 56140<br>V2 - Slight Variation   | Prairie Oak 56240<br>V3 - Moderate Variation  | Plains Oak 56250<br>V3 - Moderate Variation   |




Ridgeline Oak 56504  
V3 - Moderate Variation




Range Oak 56506  
V2 - Slight Variation




Smoky Oak 56516  
LRV 27.6 | L\* 59.52  
V3 - Moderate Variation




Forest Walnut 56703  
V2 - Slight Variation



Pinecone Oak 56720  
LRV 21.2 | L\* 53.13  
V3 - Moderate Variation



Ravine Oak 56730  
V2 - Slight Variation



Traverse Oak 56760  
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

