


Branching Out Coretec 20 Mil

Collection	Branching Out	
Style Number	4309V	
class	Class III, Type B	
Attached Underlayment	Pad	
Finish	ExoGuard+®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 122 cm l
Actual Dimensions	6.92 in w x 48.03 in l	17.58 cm w x 122.00 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Product Thickness	0.217 in	5.5 mm
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating Or Direct Glue	
Recommended Adhesive	, 4200 Resilient Tile 4 Gallon, 4200 Reslient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Pieces Per Box	10 pcs	
Area Per Box	23.11 sq ft	2.15 sq m
Weight Per Box	43.66 lbs	19.8 kg

Recommended Installation Method



Coordinating Products

LVT: Branching Out 5mm Acoustic, Branching Out 5.0 Mm
COREtec: Branching Out Coretec 12 Mil

Performance + Testing

Residual Indentation (Astm F1914)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Radiant Panel (Astm E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Attributes + Certifications

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin China

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.



Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Alpine Oak 56100 V3 - Moderate Variation</div>	 <div>Zion Oak 56103 V2 - Slight Variation</div>	 <div>Rise Oak 56120 V3 - Moderate Variation</div>	 <div>Riverside Oak 56140 V2 - Slight Variation</div>	 <div>Prairie Oak 56240 V3 - Moderate Variation</div>	 <div>Plains Oak 56250 V3 - Moderate Variation</div>
 <div>Ridgeline Oak 56504 V3 - Moderate Variation</div>	 <div>Range Oak 56506 V2 - Slight Variation</div>	 <div>Smoky Oak 56516 LRV 27.6 L* 59.52 V3 - Moderate Variation</div>	 <div>Forest Walnut 56703 V2 - Slight Variation</div>	 <div>Pinecone Oak 56720 LRV 21.2 L* 53.13 V3 - Moderate Variation</div>	 <div>Ravine Oak 56730 V2 - Slight Variation</div>



Traverse Oak 56760
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

