

Branching Out Coretec 20 Mil


| | | |
|-----------------------|---|--------------------------|
| Collection | Branching Out | |
| Style Number | 4309V | |
| Class / ASTM F3261 | Class III, Type B | |
| Attached Underlayment | Pad | |
| Finish | ExoGuard+® | |
| | U.s. | Metric |
| Nominal Dimensions | 7 in w x 48 in l | 18 cm w x 122 cm l |
| Actual Dimensions | 6.92 in w x 48.03 in l | 17.58 cm w x 122.00 cm l |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Thickness | 0.217 in | 5.5 mm |
| Edge Profile | Micro-Bevel | |
| Installation Type | Click | |
| Installation | Floating Or Direct Glue | |
| Recommended Adhesive | , 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|-------------------|-------------|-----------|
| Pieces Per Carton | 10 pcs | |
| Area Per Carton | 23.11 sq ft | 2.15 sq m |
| Weight Per Carton | 43.66 lbs | 19.8 kg |



Recommended Installation Method



Performance + Testing

| | |
|-----------------------------------|-----------------|
| Residual Indentation (ASTM F1914) | Passes |
| Resistance to Heat (ASTM F1514) | Passes |
| Resistance to Light (ASTM F1515) | Passes |
| Radiant Panel (ASTM E648) | Passes, Class I |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)

Material Health & Environmental Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Indoor Air Quality | FloorScore® Certified |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 20.5 Kg Co ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | Country of Origin China |
| Global GreenTag International | Phd Health Rate - Platinum |
| | Best Environmental Practice Pvc - Version 2.0 |

WELL V2 Contribution Credit

| | |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | Absence of Halogenated Flame Retardants |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt | Ortho-Phthalates |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt | FloorScore Certificate |

Green Leed Contribution Credit

| | |
|--|---|
| MR Credit: Building Product Disclosure and Optimization | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | FloorScore® Certified |
| EQ Credit: Low Emitting Materials | |
| Option 1: Product Category Calculations | |

Installation Guidelines

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Alpine Oak 56100 V3 - Moderate Variation | Zion Oak 56103 V2 - Slight Variation | Rise Oak 56120 V3 - Moderate Variation | Riverside Oak 56140 V2 - Slight Variation | Prairie Oak 56240 V3 - Moderate Variation | Plains Oak 56250 V3 - Moderate Variation |



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

