


Branching Out Coretec 20 Mil

Colección	Branching Out	
Número De Estilo	4309V	
clase	Class III, Type B	
Manta Inferior Adicional	Almohadilla	
Terminación	ExoGuard+®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensiones Reales	6.92 in w x 48.03 in l	17.58 cm w x 122.00 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.217 in	5.5 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating Or Direct Glue	
Adhesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Piezas Por Caja	10 pcs	
Área Por Caja	23.11 sq ft	2.15 sq m
Peso Por Caja	43.66 lbs	19.8 kg

Método De Instalación Recomendado



Productos Que Combinan

COREtec: Branching Out Coretec 12 Mil  
LVT: Branching Out 5mm Acoustic, Branching Out 5.0 Mm

desempeño + pruebas

margen adicional residual (ASTM F1914)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
panel radiante (ASTM E648)	Passes, Class I



Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)

Atributos + Certificaciones

Health & Wellbeing

Indoor Air Quality

FloorScore® | Certificado

Climate Impact

Environmental Product Declaration (EPD)

Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017

Embodied Carbon (Cradle to Gate)

20.5 Kg Co<sub>2</sub>/M<sup>2</sup>

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition  
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt  
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt  
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt  
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

**Absence of Asbestos**  
**Absence of Heavy Metals**  
**Absence of Halogenated Flame Retardants**  
  
**Ortho-Phthalates**  
**FloorScore Certificate**

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción  
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)  
Crédito EQ: Materiales de baja emisión  
Opción 1: Cálculos de categoría de producto

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
  
**FloorScore® Certified**

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Alpine Oak 56100  
V3 - Moderate Variation



Zion Oak 56103  
V2 - Slight Variation



Rise Oak 56120  
V3 - Moderate Variation



Riverside Oak 56140  
V2 - Slight Variation



Prairie Oak 56240  
V3 - Moderate Variation



Plains Oak 56250  
V3 - Moderate Variation



Ridgeline Oak 56504  
V3 - Moderate Variation



Range Oak 56506  
V2 - Slight Variation



Smoky Oak 56516  
LRV 27.6 | L\* 59.52  
V3 - Moderate Variation



Forest Walnut 56703  
V2 - Slight Variation



Pinecone Oak 56720  
LRV 21.2 | L\* 53.13  
V3 - Moderate Variation



Ravine Oak 56730  
V2 - Slight Variation



Traverse Oak 56760  
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

