


Branching Out Coretec 20 Mil

Colección	Branching Out	
Número De Estilo	4309V	
clase	Class III, Type B	
Manta Inferior Adicional	Almohadilla	
Terminación	ExoGuard+®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensiones Reales	6.92 in w x 48.03 in l	17.58 cm w x 122.00 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.217 in	5.5 mm
Perfil De Borde	Micro-Biselado	
Installation Type	Click	
Instalación	Floating Or Direct Glue	
Adhesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 4200 Reslient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Piezas Por Caja	10 pcs	
Área Por Caja	23.11 sq ft	2.15 sq m
Peso Por Caja	43.66 lbs	19.8 kg

Método De Instalación Recomendado



Productos Que Combinan

LVT: Branching Out 5mm Acoustic, Branching Out 5.0 Mm
COREtec: Branching Out Coretec 12 Mil

Desempeño + Pruebas

Margen Adicional Residual (Astm F1914)	Passes
Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Panel Radiante (Astm E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	Country of Origin China

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore Certified

[Installation Guidelines](#)
[Maintenance Guidelines](#)


Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Alpine Oak 56100 V3 - Moderate Variation	Zion Oak 56103 V2 - Slight Variation	Rise Oak 56120 V3 - Moderate Variation	Riverside Oak 56140 V2 - Slight Variation	Prairie Oak 56240 V3 - Moderate Variation	Plains Oak 56250 V3 - Moderate Variation
					
Ridgeline Oak 56504 V3 - Moderate Variation	Range Oak 56506 V2 - Slight Variation	Smoky Oak 56516 LRV 27.6 L* 59.52 V3 - Moderate Variation	Forest Walnut 56703 V2 - Slight Variation	Pinecone Oak 56720 LRV 21.2 L* 53.13 V3 - Moderate Variation	Ravine Oak 56730 V2 - Slight Variation



Traverse Oak 56760
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

