


Branching Out Coretec 20 Mil

| | | |
|-------------------|--|--------------------------|
| コレクション | Branching Out | |
| スタイルナンバー | 4309V | |
| クラス | Class III, Type B | |
| 付属下敷 | パッド | |
| 仕上げ | ExoGuard+® | |
| | 米国 | メートル法 |
| 公称寸法 | 7 in w x 48 in l | 18 cm w x 122 cm l |
| 実際の寸法 | 6.92 in w x 48.03 in l | 17.58 cm w x 122.00 cm l |
| 摩耗層の厚さ | 20 mil (0.02 in) | 0.51 mm |
| 製品全体の厚さ | 0.217 in | 5.5 mm |
| エッジプロファイル | マイクロベベル | |
| Installation Type | Click | |
| インストール | Floating Or Direct Glue | |
| 推奨接着剤 | , 4200 Resilient Tile 4 Gallon, 4200 Reslient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

包装

| | | |
|------------|-------------|-----------|
| ボックスあたりの個数 | 10 pcs | |
| ボックスあたりの面積 | 23.11 sq ft | 2.15 sq m |
| ボックスあたりの重量 | 43.66 lbs | 19.8 kg |

推奨インストール方法



コーディネート商品

COREtec: Branching Out Coretec 12 Mil, Branching Out WPC

パフォーマンス + テスト

| | |
|-------------------|-----------------|
| 残留圧痕 (astm F1914) | Passes |
| 耐熱性 (astm F1514) | Passes |
| 耐光性 (astm F1515) | Passes |
| 放射パネル (astm E648) | Passes, Class I |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証

属性+認定

| | |
|---|---|
| Health & Wellbeing | |
| Indoor Air Quality | FloorScore® 認証取得 |
| Climate Impact | |
| Environmental Product Declaration (EPD) | ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得 |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | Country of Origin 中国 |

グリーンリード貢献クレジット


| | |
|--|--|
| MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| EQクレジット：低排出材料 オプション1：製品カテゴリの計算 | FloorScore Certified |
| Installation Guidelines | Please visit www.shawcontract.com for the most current warranty information. |
| Maintenance Guidelines | Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. |


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Alpine Oak 56100 V3 - Moderate Variation | Zion Oak 56103 V2 - Slight Variation | Rise Oak 56120 V3 - Moderate Variation | Riverside Oak 56140 V2 - Slight Variation | Prairie Oak 56240 V3 - Moderate Variation | Plains Oak 56250 V3 - Moderate Variation |
|  |  |  |  |  |  |
| Ridgeline Oak 56504 V3 - Moderate Variation | Range Oak 56506 V2 - Slight Variation | Smoky Oak 56516 LRV 27.6 L* 59.52 V3 - Moderate Variation | Forest Walnut 56703 V2 - Slight Variation | Pinecone Oak 56720 LRV 21.2 L* 53.13 V3 - Moderate Variation | Ravine Oak 56730 V2 - Slight Variation |



Traverse Oak 56760
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

