


Branching Out Coretec 12 Mil

Coleção	Branching Out	
Número Do Produto	4308V	
classe	Class III, Type B	
Manta Inferior Adicional	Pad	
Acabamento	ExoGuard+®	
	U.s.	Metric
Dimensões Nominais	7 in w x 48 in l	18 cm w x 122 cm l
Dimensões Reais	6.92 in w x 48.03 in l	17.58 cm w x 122.00 cm l
Espessura Da Camada De Uso	12 mil (0.012 in)	0.3 mm
Espessura Total Do Produto	0.173 in	4.4 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Click	
Instalação	Floating Or Direct Glue	
Adesivo Recomendado	, 4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Empacotamento

Peças Por Caixa	12 pcs	
Área Por Caixa	27.73 sq ft	2.58 sq m
Peso Por Caixa	41.32 lbs	18.74 kg

Método De Instalação Recomendado



Produtos Coordenados

COREtec: Branching Out Coretec 20 Mil
LVT: Branching Out 5mm Acoustic, Branching Out 5.0 Mm

desempenho + teste

recuo residual (ASTM F1914)	Passes
resistência ao calor (ASTM F1514)	Passes
resistência à luz (ASTM F1515)	Passes
painel radiante (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

Atributos + Certificações

Health & Wellbeing

Indoor Air Quality

FloorScore® | Certificado

Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition

X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt

X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt

Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt

X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos**Absence of Heavy Metals****Absence of Halogenated Flame Retardants****Ortho-Phthalates****FloorScore Certificate**

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção

Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)

Crédito de EQ: Materiais de baixa emissão

Opção 1: cálculos de categoria de produto










3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**FloorScore® Certified**[Installation Guidelines](#)[Maintenance Guidelines](#)Please visit www.shawcontract.com for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

Alpine Oak 56100
V3 - Moderate VariationZion Oak 56103
V2 - Slight VariationRise Oak 56120
V3 - Moderate VariationRiverside Oak 56140
V2 - Slight VariationPrairie Oak 56240
V3 - Moderate VariationPlains Oak 56250
V3 - Moderate VariationRidgeline Oak 56504
V3 - Moderate VariationRange Oak 56506
V2 - Slight VariationSmoky Oak 56516
V3 - Moderate VariationForest Walnut 56703
V2 - Slight VariationPinecone Oak 56720
V3 - Moderate VariationRavine Oak 56730
V2 - Slight Variation



Traverse Oak 56760
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

