

Branching Out Coretec 12 Mil


Collection	Branching Out	
Numéro De Style	4308V	
classe	Class III, Type B	
Endos Intégrée	Tampon	
Finition	ExoGuard+®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 48 in l	18 cm w x 122 cm l
Dimensions Réelles	6.92 in w x 48.03 in l	17.58 cm w x 122.00 cm l
Épaisseur De La Couche d'Usure	12 mil (0.012 in)	0.3 mm
Épaisseur Générale Du Produit	0.173 in	4.4 mm
Profil Du Bord	Micro-Biseau	
Installation Type	Click	
Installation	Floating Or Direct Glue	
Adhésif Recommandé	4200 Resilient Tile 4 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Emballage

Pièces Par Carton	12 pcs	
Surface Par Carton	27.73 sq ft	2.58 sq m
Poids Par Carton	41.32 lbs	18.74 kg



Méthodes d'Installation Conseillées



Coordination Des Produits

LVT: Branching Out 5mm Acoustic, Branching Out 5.0 Mm

COREtec: Branching Out Coretec 20 Mil

Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 10 Ans](#)

Attributs + Certifications

Climate Impact

Environmental Product Declaration (EPD)

Total Recycled Content

Global Product Assessment

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017  
0% (Pre-Consumer 0% | Post-Consumer 0%)

FloorScore® | Agréé  
Greenguard (Certification, Gold, Private Label) | Agréé  
Country of Origin | Imported

Contribution Au Certificat Vert Leed

« Crédit MR : Divulgation et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore & Greenguard Gold Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Alpine Oak 56100 V3 - Moderate Variation	Zion Oak 56103 V2 - Slight Variation	Rise Oak 56120 V3 - Moderate Variation	Riverside Oak 56140 V2 - Slight Variation	Prairie Oak 56240 V3 - Moderate Variation	Plains Oak 56250 V3 - Moderate Variation
					
Ridgeline Oak 56504 V3 - Moderate Variation	Range Oak 56506 V2 - Slight Variation	Smoky Oak 56516 V3 - Moderate Variation	Forest Walnut 56703 V2 - Slight Variation	Pinecone Oak 56720 V3 - Moderate Variation	Ravine Oak 56730 V2 - Slight Variation



Traverse Oak 56760  
V3 - Moderate Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

