

## Origin


Collection	<b>Mineralfloor</b>	
Style Number	<b>4338V</b>	
Construction	<b>Rigid Mineral Core With Inline Level Edge Profile</b>	
Class / ASTM F3261	<b>Class I, Type B</b>	
	U.s.	Metric
Nominal Dimensions	<b>6 in w x 48 in l</b>	<b>14 cm w x 121 cm l</b>
Actual Dimensions	<b>5.66 in w x 47.55 in l</b>	<b>14.38 cm w x 120.78 cm l</b>
Overall Thickness	<b>0.236 in</b>	<b>6 mm</b>
Edge Profile	<b>Bevel</b>	
Installation Type	<b>InLine Level Edge</b>	
Installation	<b>Direct Glue</b>	
Recommended Adhesive	<b>3 in 1 Ultra Rigid Mineral Core 4 Gallon</b>	

### Packaging

Pieces Per Carton	<b>12 pcs</b>	
Area Per Carton	<b>22.46 sq ft</b>	<b>2.09 sq m</b>
Weight Per Carton	<b>39.91 lbs</b>	<b>18.1 kg</b>



### Recommended Installation Method



### Coordinating Products

Rigid Core: Basis

Performance + Testing

Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662, Flaming Mode)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Warranties

15 Year Commercial Limited

Material Health & Environmental Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certified
Climate Impact	
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	FloorScore® Certified
EQ Credit: Low Emitting Materials	
Option 1: Product Category Calculations	

Installation Guidelines

Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Distinct 38115  
V3 - Moderate Variation



Initiate 38130  
V2 - Slight Variation



Theory 38140  
V2 - Slight Variation



Inherent 38700  
V3 - Moderate Variation



Prelude 38710  
V2 - Slight Variation



Composition 38720  
V2 - Slight Variation



Overture 38760  
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

