

## Origin


Colección	<b>Mineralfloor</b>	
Número De Estilo	<b>4338V</b>	
Construcción	<b>Rigid Mineral Core With Inline Level Edge Profile</b>	
clase	<b>Class I, Type B</b>	
	U.s.	Metric
Dimensiones Nominales	<b>6 in w x 48 in l</b>	<b>14 cm w x 121 cm l</b>
Dimensiones Reales	<b>5.66 in w x 47.55 in l</b>	<b>14.38 cm w x 120.78 cm l</b>
Espesor Total Del Producto	<b>0.236 in</b>	<b>6 mm</b>
Perfil De Borde	<b>Biselado</b>	
Installation Type	<b>InLine Level Edge</b>	
Instalación	<b>Direct Glue</b>	
Adhesivo Recomendado	<b>3 in 1 Ultra Rigid Mineral Core 4 Gallon</b>	

## Embalaje

Piezas Por Caja	<b>12 pcs</b>	
Área Por Caja	<b>22.46 sq ft</b>	<b>2.09 sq m</b>
Peso Por Caja	<b>39.91 lbs</b>	<b>18.1 kg</b>



## Método De Instalación Recomendado



## Productos Que Combinan

Rigid Core: Basis

desempeño + pruebas

margen adicional residual (ASTM F1914)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
densidad de humo (ASTM E662, modo flameado)	Passes
panel radiante (ASTM E648)	Passes, Class I
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.	

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore® Certified
Installation Guidelines	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.
Maintenance Guidelines	

Available Colorways



Distinct 38115  
V3 - Moderate Variation



Initiate 38130  
V2 - Slight Variation



Theory 38140  
V2 - Slight Variation



Inherent 38700  
V3 - Moderate Variation



Prelude 38710  
V2 - Slight Variation



Composition 38720  
V2 - Slight Variation



Overture 38760  
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

