

Origin


Collection	<b>Mineralfloor</b>	
Style Number	<b>4338V</b>	
Construction	<b>Rigid Mineral Core With Inline Level Edge Profile</b>	
Class / ASTM F3261	<b>Class I, Type B</b>	
	U.s.	Metric
Nominal Dimensions	<b>6 in w x 48 in l</b>	<b>14 cm w x 121 cm l</b>
Actual Dimensions	<b>5.66 in w x 47.55 in l</b>	<b>14.38 cm w x 120.78 cm l</b>
Overall Thickness	<b>0.236 in</b>	<b>6 mm</b>
Edge Profile	<b>Bevel</b>	
Installation Type	<b>InLine Level Edge</b>	
Installation	<b>Direct Glue</b>	
Recommended Adhesive	<b>3 in 1 Ultra Rigid Mineral Core 4 Gallon</b>	

Packaging

Pieces Per Carton	<b>12 pcs</b>	
Area Per Carton	<b>22.46 sq ft</b>	<b>2.09 sq m</b>
Weight Per Carton	<b>39.91 lbs</b>	<b>18.1 kg</b>



Recommended Installation Method



Coordinating Products

None: Basis

Performance + Testing

Resistance To Heat (Astm F1514)	<b>Passes</b>
Resistance To Light (Astm F1515)	<b>Passes</b>
Resistance To Chemicals (Astm F925)	<b>Passes</b>
Coefficient Of Friction (Astm D2407, Slip Resistance)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)

Material Health & Environmental Certifications

Climate Impact

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certified

Country of Origin | China

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)  
EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore Certified**

[Installation Guidelines](#)

Maintenance Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Distinct 38115  
V3 - Moderate Variation



Initiate 38130  
V2 - Slight Variation



Theory 38140  
V2 - Slight Variation



Inherent 38700  
V3 - Moderate Variation



Prelude 38710  
V2 - Slight Variation




Composition 38720  
V2 - Slight Variation





Overture 38760  
V2 - Slight Variation


Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1  
  
Uniform Appearance

V2  
  
Slight Variation

V3  
  
Moderate Variation

V4  
  
Substantial Variation

