


Vitality Hues

Collection	Vitality	
Style Number	4376V	
Welding Rod Style Number	184CA	
Construction class	Commercial Homogeneous Sheet	
Finish	ExoGuard®	
Overall Product Thickness	U.S.	Metric
	0.079 in	2 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	
Packaging		
Actual Roll Size	6.56 ft w x 65.62 ft l	2.00 m w x 20.00 m l
Area Per Roll	47.84 sy/roll	40 sq m/roll
Weight Per Roll	246.92 lbs	112 kg



Recommended Installation Method



Coordinating Products

Sheet: Vitality Sheet, Vitality Tones

performance + testing

residual indentation (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
radiant panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes
Static Electrical Propensity (EN 1815), Bacterial Resistance (ISO 846 Part C) and Particle Emission (ISO 14664-1)	Additional Test Information

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributes + Certifications

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)
Life-Cycle Carbon Emissions
Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
5.9 Kg CO₂/M²
Low Embodied Carbon
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore® Certified

[Installation Guidelines](#)

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.







Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Replenish 00100 Weldrod 00100</div>	 <div>Share 00104 Weldrod 00104</div>	 <div>Produce 00105 Weldrod 00105</div>	 <div>Animate 00110 Weldrod 00110</div>	 <div>Uphold 00111 Weldrod 00111</div>	 <div>Dash 00114 Weldrod 00114</div>
 <div>Drive 00120 Weldrod 00120</div>	 <div>Excite 00121 Weldrod 00121</div>	 <div>Nurture 00130 Weldrod 00130</div>	 <div>Spright 00144 Weldrod 00144</div>	 <div>Prevail 00155 Weldrod 00155</div>	 <div>Zing 00211 Weldrod 00211</div>
 <div>Spirit 00323 Weldrod 00323</div>	 <div>Vigor 00325 Weldrod 00325</div>	 <div>Verve 00326 Weldrod 00326</div>	 <div>Pizazz 00327 Weldrod 00327</div>	 <div>Excel 00330 Weldrod 00330</div>	 <div>Ease 00350 Weldrod 00350</div>
 <div>Gusto 00405 Weldrod 00405</div>	 <div>Moxie 00411 Weldrod 00411</div>	 <div>Dream 00415 Weldrod 00415</div>	 <div>Exuberance 00490 Weldrod 00490</div>	 <div>Assist 00496 Weldrod 00496</div>	 <div>Sustain 00515 Weldrod 00515</div>
 <div>Prosper 00518 Weldrod 00518</div>	 <div>Foster 00520 Weldrod 00520</div>	 <div>Encourage 00535 Weldrod 00535</div>	 <div>Champion 00560 Weldrod 00560</div>	 <div>Fire 00668 Weldrod 00668</div>	 <div>Fervor 00675 Weldrod 00675</div>

ShawContract®

Vitality Hues

					
Sparkle 00700 Weldrod 00700	Vim 00750 Weldrod 00750	Goodness 00761 Weldrod 00761	Pride 00860 Weldrod 00860	Power 00865 Weldrod 00865	Passion 00991 Weldrod 00991

