

Vitality Hues

Collection	Vitality	
Style Number	4376V	
Welding Rod Style Number	184CA	
Construction class	Commercial Homogeneous Sheet	
Finish	ExoGuard®	
Overall Product Thickness	U.S.	Metric
	0.079 in	2 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	
Packaging		
Actual Roll Size	6.56 ft w x 65.62 ft l	2.00 m w x 20.00 m l
Area Per Roll	47.84 sy/roll	40 sq m/roll
Weight Per Roll	246.92 lbs	112 kg



Recommended Installation Method



Reverse

Coordinating Products

Sheet: Vitality Sheet, Vitality Tones

Performance + Testing

Residual Indentation (Astm F1914)	Passes
Flexibility (Astm F137)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Resistance To Chemicals (Astm F925)	Passes
Coefficient Of Friction (Astm D2407, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Attributes + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	7.04 Kg CO ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	FloorScore® Certified Country of Origin Imported

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	Health Product Declaration (HPD) 100 Ppm Disclosure
MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified

[Installation Guidelines](#)

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.







Visit shawcontract.com/testing for more information.

Available Colorways

					
Replenish 00100 Weldrod 00100	Share 00104 Weldrod 00104	Produce 00105 Weldrod 00105	Animate 00110 Weldrod 00110	Uphold 00111 Weldrod 00111	Dash 00114 Weldrod 00114
					
Drive 00120 Weldrod 00120	Excite 00121 Weldrod 00121	Nurture 00130 Weldrod 00130	Spright 00144 Weldrod 00144	Prevail 00155 Weldrod 00155	Zing 00211 Weldrod 00211
					
Spirit 00323 Weldrod 00323	Vigor 00325 Weldrod 00325	Verve 00326 Weldrod 00326	Pizazz 00327 Weldrod 00327	Excel 00330 Weldrod 00330	Ease 00350 Weldrod 00350
					
Gusto 00405 Weldrod 00405	Moxie 00411 Weldrod 00411	Dream 00415 Weldrod 00415	Exuberance 00490 Weldrod 00490	Assist 00496 Weldrod 00496	Sustain 00515 Weldrod 00515
					
Prosper 00518 Weldrod 00518	Foster 00520 Weldrod 00520	Encourage 00535 Weldrod 00535	Champion 00560 Weldrod 00560	Fire 00668 Weldrod 00668	Fervor 00675 Weldrod 00675

ShawContract®

Vitality Hues

					
Sparkle 00700 Weldrod 00700	Vim 00750 Weldrod 00750	Goodness 00761 Weldrod 00761	Pride 00860 Weldrod 00860	Power 00865 Weldrod 00865	Passion 00991 Weldrod 00991

