

Vitality Tones


Colección	Vitality	
Número De Estilo	4375V	
Número De Estilo De Barra De Soldadura	184CA	
Construcción clase	Manta Vinílica Comercial Homogénea	
Terminación	ExoGuard®	
	U.s.	Metric
Espesor Total Del Producto	0.079 in	2 mm
Installation Type	Dry Back	
Instalación	Direct Glue	
Adhesivo Recomendado	S150-95 Resilient Sheet Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient Sheet or 4151 Multi-Use Premium	

Embalaje

Tamaño Real Del Rollo	6.56 ft w x 65.62 ft l	2.00 m w x 20.00 m l
Área Por Rollo	47.84 sy/roll	40 sq m/roll
Peso Por Rollo	286.6 lbs	130 kg



Método De Instalación Recomendado



Productos Que Combinan

Sheet: Vitality Sheet, Vitality Hues

desempeño + pruebas

margen adicional residual (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
panel radiante (ASTM E648)	Passes, Class I
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificaciones

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

[Health Product Declaration \(HPD\) | 1000 ppm Disclosure](#)
[FloorScore® | Certificado](#)

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)
Life-Cycle Carbon Emissions
Total Recycled Content

[Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017](#)
5.9 Kg Co₂/M²
Low Embodied Carbon
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

[Country of Origin | Imported](#)

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción
Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales
Crédito MR: Divulgación y optimización de productos de construcción
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)
Crédito EQ: Materiales de baja emisión
Opción 1: Cálculos de categoría de producto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore® Certified

[Installation Guidelines](#)













[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

[Visit shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

 <div>Root 00100 Weldrod 0100D</div>	 <div>Brawn 00104 Weldrod 0104D</div>	 <div>Cheer 00105 Weldrod 0105D</div>	 <div>Pep Up 00111 Weldrod 0111D</div>	 <div>Sing 00120 Weldrod 0120D</div>	 <div>Humor 00130 Weldrod 00130</div>
 <div>Ginger 00144 Weldrod 0144D</div>	 <div>Play 00163 Weldrod 00163</div>	 <div>Mettle 00240 Weldrod 00240</div>	 <div>Amp Up 00485 Weldrod 00485</div>	 <div>Jazz Up 00515 Weldrod 00515D</div>	 <div>Might 00520 Weldrod 00520D</div>

