

Vitality Tones

| | | |
|---------------------------------------|---|--------|
| Coleção | Vitality | |
| Número Do Produto | 4375V | |
| Número Do Estilo Da Haste De Soldagem | 184CA | |
| Construção | Manta Homogênea Comercial | |
| classe | | |
| Acabamento | ExoGuard® | |
| | U.s. | Metric |
| Espessura Total Do Produto | 0.079 in | 2 mm |
| Installation Type | Dry Back | |
| Instalação | Direct Glue | |
| Adesivo Recomendado | S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

Empacotamento

| | | |
|----------------------|------------------------|----------------------|
| Tamanho Real Do Rolo | 6.56 ft w x 65.62 ft l | 2.00 m w x 20.00 m l |
| Área Por Rolo | 47.84 sy/roll | 40 sq m/roll |
| Peso Por Rolo | 286.6 lbs | 130 kg |



Método De Instalação Recomendado



Reverso

Produtos Coordenados

Sheet: Vitality Sheet, Vitality Hues

desempenho + teste

| | |
|---|---|
| recuo residual (ASTM F1914) | Passes |
| Flexibility (ASTM F137) | Passes |
| resistência ao calor (ASTM F1514) | Passes |
| resistência à luz (ASTM F1515) | Passes |
| resistência a produtos químicos (ASTM F925) | Passes |
| painel radiante (ASTM E648) | Passes, Class I |
| coeficiente de atrito (ASTM D2407, resistência ao deslizamento) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificações

| | |
|---|---|
| Health & Wellbeing | |
| Material Ingredient Transparency | Health Product Declaration (HPD) 1000 ppm Disclosure |
| Indoor Air Quality | FloorScore® Certificado |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 5.9 Kg Co ₂ /M ² |
| Life-Cycle Carbon Emissions | Low Embodied Carbon |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | Country of Origin Imported |

WELL V2 Contribution Credit

| | |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | Absence of Halogenated Flame Retardants |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt | Ortho-Phthalates |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt | FloorScore Certificate |

Crédito De Contribuição

| | |
|--|---|
| MR Credit: Divulgação e otimização de produtos de construção | Health Product Declaration (HPD) 100 Ppm Disclosure |
| Ingredientes materiais - Opção 1: Relatório de ingredientes materiais | |
| MR Credit: Divulgação e otimização de produtos de construção | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD) | FloorScore® Certified |
| Crédito de EQ: Materiais de baixa emissão | |
| Opção 1: cálculos de categoria de produto | |

[Installation Guidelines](#)













Maintenance Guidelines


Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|--|---|--|---|---|
|  <div>Root 00100 Weldrod 0100D</div> |  <div>Brawn 00104 Weldrod 0104D</div> |  <div>Cheer 00105 Weldrod 0105D</div> |  <div>Pep Up 00111 Weldrod 0111D</div> |  <div>Sing 00120 Weldrod 0120D</div> |  <div>Humor 00130 Weldrod 00130</div> |
|  <div>Ginger 00144 Weldrod 0144D</div> |  <div>Play 00163 Weldrod 00163</div> |  <div>Mettle 00240 Weldrod 00240</div> |  <div>Amp Up 00485 Weldrod 00485</div> |  <div>Jazz Up 00515 Weldrod 00515D</div> |  <div>Might 00520 Weldrod 00520D</div> |

 Quick Ship