

Stijlnummer	4377V	
Producttype	Hoog Commercieel Gebruik Luxe Vinyl Tegel Met Glasvezel	
Collectie	Nordic	
Uitzicht	Stijlnaam	Gegevens + Prestatie
Type of Floorcovering	EN 1307	Vinyl Tile
Classificatie	ISO 10874	33 commercial heavy
Totale Massa	EN ISO 23997	9.17 kg/m²
Totale Dikte	EN ISO 24346	5 mm
Afmetingen	EN 994	18.42 cm x 121.92 cm 8 tiles (1.8 sq m) per box
Gewicht Per Doos		17.18 kg




Prestatie


Ontvlambaarheid	EN 13501-1	Bfl-S1 (unadhered testing)
Warmteweerstand m² K/w	ISO 8302	0.018 m² K/W
Elektrostatische Weerstand	EN 1815	≤ 2.0 kV (stroll test)
Slipweerstand	BS 7976-2	
	DIN 51130	R9 (shod ramp)
Dimensionale Stabiliteit	EN ISO 23999	≤0.15%
Stoel Met Wieltjes	EN 425, ISO 4918	continuous use
Resterende Indeuiking	EN ISO 24343-1	.08 mm
Contactgeluidreductie	BS EN ISO 10140	ΔLw 9dB/21dB with 2mm underlay
Geluidsabsorptie	ISO 354	
Kleurvastheid Voor Licht	BS EN ISO 105-BO2	7-8

15 Jaar Commercieel Beperkt, Commercial 15 Year Underbed Bond Warranty subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.

Aanbevolen Installatiemethode




colour and visual variation index



Coördinerende Producten

LVT: Nordic 2.5



ΔLw 9dB/21dB with 2mm underlay

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +61 800 556 302

CE

22

EU.DOP/1658/CPR/1222/1222/LVT

SHAW EUROPE LIMITED VAARTWEG 10, 4905 BL

NETHERLANDS (NLD)

Notified Body 1658

UK

CA

22

UK.DOP/0321/CPR/1222/1222/LVT

SHAW EUROPE LIMITED BLACKADDIE RD,

SANQUHAR DG4 6DB, UNITED KINGDOM

Approved Body 1658

E1

HCHO

Bfl-s1

For use as an indoor floor covering as specified by the manufacturer

producttransparantie

Shaw Contract streeft ernaar klanten een bouwchemie bieden die veilig en betrouwbaar is. Samen zullen wij u helpen om uw doelstellingen op het gebied van materiaalgezondheid te bereiken. Luxe Vinyl

Kenmerken + Certificeringen

Health Product Declaration (HPD)	1000 ppm Disclosure
Environmental Product Declaration (EPD)	3de Partij Gecertificeerd in Overeenstemming Met ISO 14025, EN 15804, & ISO 21930:2017
FloorScore®	Gecertificeerd
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
land van herkomst	China

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	FloorScore Certificate
X14 Material Transparency Part 1: Promote Ingredient Disclosure Optimization	Health Product Declaration (HPD) 1000 Ppm Disclosure

Groen Leed Bijdragekrediet

"MR-krediet: Openbaarmaking en optimalisering van bouwproducten Materiaalingrediënten - Optie 1: Rapportage materiaalingrediënten"	Health Product Declaration (HPD) 100 Ppm Disclosure
"MR-krediet: openbaarmaking en optimalisering van bouwproducten Milieuproductverklaringen - Optie 1: Milieuproductverklaring (EPD)"	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
"EQ-krediet: materialen met lage emissie Optie 1: Berekeningen per productcategorie"	FloorScore Certified

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Lichtreflectiewaarde

					
Honey 77103 LRV 26.8 L* 58.83 V2 - Slight Variation	Alder 77104 LRV 25.5 L* 57.57 V3 - Moderate Variation	Blonde 77112 LRV 37.6 L* 67.73 V2 - Slight Variation	Driftwood 77120 LRV 30.6 L* 62.16 V3 - Moderate Variation	Birch 77140 LRV 35.8 L* 66.35 V2 - Slight Variation	Fir 77155 LRV 42 L* 70.85 V2 - Slight Variation
					
Radiant 77710 LRV 21.1 L* 53.08 V2 - Slight Variation	Redwood 77720 LRV 22 L* 54.07 V2 - Slight Variation	Elm 77721 LRV 22.7 L* 54.81 V2 - Slight Variation	Golden 77756 LRV 15.2 L* 45.94 V3 - Moderate Variation		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

