

Innate Linen Sheet

Collection	Innate + In Tandem	
Style Number	4366V	
Welding Rod Style Number	270VS	
Construction	Comm Bio-Based Polyurethane Het Sheet W/Fiberglass	
class	Tested To ASTM 1303	
Finish	ExoGuard+®	
	U.s.	Metric
Overall Product Thickness	0.098 in	2.5 mm
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	
Packaging		
Actual Roll Size	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
Area Per Roll	48.08 sy/roll	40.2 sq m/roll
Weight Per Roll	321.88 lbs	146 kg



Recommended Installation Method



Non Reverse

Coordinating Products

None: Innate, In Tandem Sheet, In Tandem, Innate Sheet, Innate Stria Tile

Performance + Testing

Residual Indentation (Astm F1914)	Passes
Flexibility (Astm F137)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Resistance To Chemicals (Astm F925)	Passes
Coefficient Of Friction (Astm D2407, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited
[Commercial 15 Year Underbed Bond Warranty](#)

Attributes + Certifications

Health & Wellbeing

Material Ingredient Transparency

Cradle to Cradle Certified™ | Silver Level (Version 3.1)
Health Product Declaration (HPD) | 1000 ppm Disclosure
Declare | LBC Compliant

Climate Impact

Environmental Product Declaration (EPD)
Embodied Carbon (Cradle to Gate)
Life-Cycle Carbon Emissions
Total Recycled Content

3rd Party Certified in Accordance with EN 15804, ISO 14025
4.31 Kg Co₂/M²
Carbon Neutral
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certified
CE Marking (EN 14041) | 3rd Party Certified
Greenguard (Certification, Gold, Private Label) | Certified
Country of Origin | Imported

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting
MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)
EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with EN 15804, ISO 14025

FloorScore & Greenguard Gold Certified

Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply
and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of
this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

Air 66104
Weldrod 00100

Sand 66105
Weldrod 00101

Bare 66111
Weldrod 00111

Earth 66130
Weldrod 00126

Shore 66405
Weldrod 00405

Sea 66416
Weldrod 00416

