


Innate Linen Sheet

Colección	Innate + In Tandem	
Número De Estilo	4366V	
Número De Estilo De Barra De Soldadura	270VS	
clase	Tested To ASTM 1303	
Terminación	ExoGuard+®	
	U.s.	Metric
Espesor Total Del Producto	0.098 in	2.5 mm
Installation Type	Dry Back	
Instalación	Direct Glue	
Adhesivo Recomendado	4200 Reslient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	
Embalaje		
Tamaño Real Del Rollo	6.59 ft w x 65.62 ft l	2.01 m w x 20.00 m l
Área Por Rollo	48.08 sy/roll	40.2 sq m/roll
Peso Por Rollo	321.88 lbs	146 kg



Método De Instalación Recomendado



Productos Que Combinan

None: Innate, In Tandem Sheet, In Tandem, Innate Sheet, Innate Stria Tile

Desempeño + Pruebas

Margen Adicional Residual (Astm F1914)	Passes
Flexibilidad (Astm F137)	Passes
Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Resistencia A Productos Químicos (Astm F925)	Passes
Coefficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Atributos + Certificaciones

Health & Wellbeing

Material Ingredient Transparency

Cradle to Cradle Certified™ | Nivel Plata (Versión 3.1)  
Health Product Declaration (HPD) | 1000 ppm Disclosure  
Declare | Compatible LBC

Climate Impact

Environmental Product Declaration (EPD)

Certificado Tercerizado De Acuerdo Con La Norma EN 15804, ISO 14025

Embodied Carbon (Cradle to Gate)

4.31 Kg Co<sub>2</sub>/M<sup>2</sup>

Life-Cycle Carbon Emissions

Carbon Neutral

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certificado  
CE Marking (EN 14041) | Certificado Tercerizado  
Greenguard (Certification, Gold, Private Label) | Certificado  
Country of Origin | Imported

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción  
Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales

Crédito MR: Divulgación y optimización de productos de construcción  
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)

Crédito EQ: Materiales de baja emisión  
Opción 1: Cálculos de categoría de producto

Installation Guidelines

**Health Product Declaration (HPD) | 100 Ppm Disclosure**

**3rd Party Certified in Accordance with EN 15804, ISO 14025**











**FloorScore & Greenguard Gold Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Air 66104 Weldrod 00100	Sand 66105 Weldrod 00101	Bare 66111 Weldrod 00111	Earth 66130 Weldrod 00126	Shore 66405 Weldrod 00405	Sea 66416 Weldrod 00416
					
Loam 66504 Weldrod 00504	Fog 66515 Weldrod 00506	Native 66516 Weldrod 00516	Serene 66518 Weldrod 00518		

