

Function 2.5

| | | |
|----------------------------|---|-------------------------|
| Colección | Function + Flow | |
| Número De Estilo | 4386V | |
| Construcción | Luxury Vinyl Tile De Uso Comercial | |
| clase | Class III, Type B | |
| Terminación | ExoGuard+® | |
| | U.s. | Metric |
| Dimensiones Nominales | 18 in w x 18 in l | 46 cm w x 46 cm l |
| Dimensiones Reales | 18.00 in w x 18.00 in l | 45.72 cm w x 45.72 cm l |
| Desgaste De La Capa De Uso | 22 mil (0.022 in) | 0.56 mm |
| Espesor Total Del Producto | 0.098 in | 2.5 mm |
| Installation Type | Dry Back | |
| Instalación | Direct Glue | |
| Adhesivo Recomendado | S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon | |

Embalaje

| | | |
|-----------------|-----------|-----------|
| Piezas Por Caja | 20 pcs | |
| Área Por Caja | 45 sq ft | 4.18 sq m |
| Peso Por Caja | 40.15 lbs | 18.21 kg |



Método De Instalación Recomendado



Productos Que Combinan

LVT: Flow 2.5, Flow 5.0, Function 5.0, Flow 5.0 Lit

Desempeño + Pruebas

| | |
|---|---|
| Margen Adicional Residual (Astm F1914) | Passes |
| Resistencia Al Calor (Astm F1514) | Passes |
| Resistencia A La Luz (Astm F1515) | Passes |
| Resistencia A Productos Químicos (Astm F925) | Passes |
| Coefficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Atributos + Certificaciones

Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2018

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certificado
Country of Origin | China

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2018

Crédito EQ: Materiales de baja emisión
Opción 1: Cálculos de categoría de producto

FloorScore Certified

[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.
Visit shawcontract.com/testing for more information.

Available Colorways




Silica 86100
LRV 57
V2 - Slight Variation




Uniform 86120
LRV 36.6
V2 - Slight Variation



Transition 86501
LRV 42.4
V2 - Slight Variation



Pebble 86504
LRV 39.9
V2 - Slight Variation



Composite 86506
LRV 25.9
V2 - Slight Variation




Blend 86515
LRV 45.5
V2 - Slight Variation




Change 86520
LRV 23.5
V2 - Slight Variation

Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1


Uniform Appearance

V2

Slight Variation

V3

Moderate Variation

V4

Substantial Variation