

Numéro Du Style	4385V	
Type De Produit	Dalle De Vinyle De Luxe Commercial	
Collection	Function + Flow	
Construction	Standard	Données + Performance
Type of Floorcovering	EN 1307	Vinyl Tile
Classification	ISO 10874	class 33 heavy commercial use
Poids Total	EN ISO 23997	4.10 kg/m²
Epaisseur Du Velours	EN ISO 24346	2.5 mm
Dimensions	EN 994	45.72 cm x 45.72 cm 20 tiles (4.18 sq m) per box
Poids Par Carton		18.21 kg

Performance

Inflamabilité	EN 13501-1	Bfl-S1
Résistance Thermique m² K/w	ISO 8302	0.013 m² K/W
Propension Electrostatique	EN 1815	≤ 2.0 kV (stroll test)
Capacités Antidérapantes	BS 7976-2	PTV Dry 46 PTV Wet 32 (pendulum)
	DIN 51130	R10
Stabilité Dimensionnelle	EN ISO 23999	≤0.15%
Chaise À Roulette	EN 425, ISO 4918	no damage
Impact Sound Reduction	BS EN ISO 10140	ΔLw 6dB/21dB with 2mm underlay
Absorption Acoustique	ISO 354	0.013 m² K/W
Résistance De La Couleur À La Lumière	BS EN ISO 105-BO2	7
Émissions	ISO 16000	Yes

Limitée Commerciale De 15 Ans subject to installation in full accordance with the manufacturer's instructions and a regular effective cleaning and maintenance programme. Second location warranties are available with the use of non-adhesive IOBAC Magtabs and Tabit accessories.

Méthodes d'Installation Conseillées

Quarter Turn

Random

Monolithic

Brick

Ashlar

colour and visual variation index

V1 uniform appearance

V2 slight variation

V3 moderate variation

V4 substantial variation

Coordination Des Produits

LVT: Function 2.5, Flow 5.0 Lit

ΔLw 6dB/21dB with 2mm underlay

22

EU.DOP/1658/CPR/1222/1222/LVT

SHAW EUROPE LIMITED VAARTWEG 10, 4905 BL

NETHERLANDS (NLD)

Notified Body 1658

22

UK.DOP/0321/CPR/1222/1222/LVT

SHAW EUROPE LIMITED BLACKADDIE RD,

SANQUHAR DG4 6DB, UNITED KINGDOM

Approved Body 1658

Transparence du produit

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. Luxury Vinyl Tile products are UL Certified with an Industry-Wide EPD and are assessed for impacts on human health and the environment.

Attributs + Certifications

Déclaration environnementale de produit (EPD)	Certifié Par Un Organisme Tiers Conformément Aux Normes ISO 14025, EN15804 & ISO 21930:2017
FloorScore®	Certifié
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
pays d'origine	Chine

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Réduction des matières dangereuses Partie 1 : Optimiser la limitation des matières dangereuses – 1 pt	Absence of Heavy Metals
X10 Réduction des composés volatils Partie 1 (A) : Optimisation de la gestion des composés organiques volatils (COV) – 1 pt	Absence of Halogenated Flame Retardants
Part 2 : Optimisation de la gestion des composés organiques semi-volatils (COSV) – 1 pt	Ortho-Phthalates
X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt	FloorScore Certificate

Contribution À La Certification Leed

MR Credit: Building Product Disclosure and Optimisation	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	FloorScore Certified
"Crédit EQ : matériaux faibles émissions	
Option 1 : calculs par catégorie de produit"	

[Installation Guidelines](#)





[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.


Indice De Réflexion Lumineuse


			
Smooth 85114 LRV 36.9 L* 67.22 V3 - Moderate Variation	Sandstone 85120 LRV 32.5 L* 63.77 V3 - Moderate Variation	Streamline 85520 LRV 25.6 L* 57.62 V3 - Moderate Variation	Molten 85585 LRV 13 L* 42.71 V3 - Moderate Variation


 Quick Ship In Stock - UK


Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1
Uniform Appearance

V2
Slight Variation

V3
Moderate Variation

V4
Substantial Variation

