


Function 5.0

コレクション	Function + Flow	
スタイルナンバー	4388V	
建設	商業用高級ビニールタイル	
クラス	Class III, Type B	
仕上げ	ExoGuard+®	
	米国	メートル法
公称寸法	18 in w x 18 in l	46 cm w x 46 cm l
実際の寸法	18.00 in w x 18.00 in l	45.72 cm w x 45.72 cm l
摩耗層の厚さ	22 mil (0.022 in)	0.56 mm
製品全体の厚さ	0.197 in	5 mm
Installation Type	Dry Back	
インストール	Direct Glue	
推奨接着剤	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 2200 Resilient Tile 1 Gallon or 4151 Multi-Use Premium 4 Gallon	

包装

ボックスあたりの個数	10 pcs	
ボックスあたりの面積	22.5 sq ft	2.09 sq m
ボックスあたりの重量	44.74 lbs	20.29 kg



推奨インストール方法



コーディネート商品

LVT: Flow 5.0 Lit

パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes
摩擦係数(astm D2407、滑り抵抗)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証
Commercial 15 Year Underbed Bond Warranty

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

属性+認定

Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	FloorScore® 認証取得 Country of Origin 中国

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言 (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQクレジット：低排出材料 オプション1：製品カテゴリの計算	FloorScore Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.

Available Colorways

					
Silica 86100 LRV 58.7	Uniform 86120 LRV 36	Transition 86501 LRV 40.8	Pebble 86504 LRV 39.3	Composite 86506 LRV 24.5	Blend 86515 LRV 44



Change 86520
LRV 24.8

